



# CBC-LOK<sup>®</sup> Tube Fittings



# The Tylok Philosophy

## Our Mission

It is our mission, at Tylok International, Inc., to continuously strive for and achieve total customer satisfaction with both our products and services.

This objective falls within the framework of the larger movement toward "Total Quality" which is derived of four elements:

- 1** **Total satisfaction of our customers**
- 2** **Make our distributors and suppliers our partners in providing the highest quality products and services**
- 3** **Create a positive environment for our employees that fosters their full potential**
- 4** **Continuous financial success of the company**

We accomplish this by maintaining an honest and ethical business relationship with our customers, suppliers and employees.

## Our Goal

Tylok's aggressive goal is to establish ourselves as an industry leader and expand our market share. This is maintained in every department within the organization. Our "total effort" will guard against losing the personal touch that makes our business enjoyable and prosperous for all involved.

## Creation of an Industry

In the mid 1940s, Cullen Crawford founded the Crawford Fitting Company. Mr. Crawford developed and patented the original flareless fitting (nut and two ferrule system), for the Crawford Fitting Company. Thus, a new and innovative industry was born making it far easier to make tubing connections. This reduces installation time and errors. Since his invention, End Users from all four corners of the globe have made billions of connections. This system provides leak proof seals and thus Mr. Crawford has been named "The founder of the flareless fitting."

## Introduction

Tylok International, Inc. offers a tube fitting line, CBC-Lok®, that is fully interchangeable with Swagelok® and Parker A-Lok®. Although it is always recommended to use all CBC-Lok® components, intermixing CBC-Lok® bodies and/or component parts with that of other manufacturers will not adversely affect sealing ability. CBC-Lok® Tube Fittings are made to strict quality control standards and cannot guarantee that of other manufacturers. CBC-Lok® Tube Fittings are proudly made in the U.S.A.

## Operation

CBC-Lok® Tube Fittings are comprised of four components: The Body, Front Ferrule (Collet), Rear Ferrule (Collet) and Nut. A leak proof seal is obtained through proper ferrule action as the ferrules are tightened onto the tubing via axial thrust provided by the nut. The front ferrule provides the leak proof seal, when the nut and ferrules are properly drawn up the specified number of turns. The rear ferrule grips the tubing preventing pull-off. The stainless steel nuts are silver plated and a dry film lubricant is applied, reducing torque and ensuring proper sealing.

## Ty-Cor™ Process

Ty-Cor™ refers to the treatment which diffuses carbon into the surface of the stainless steel, thereby increasing the surface hardness without affecting the quality of the metal treated. In fact, when AISI 316 stainless steel is treated, the corrosion resistance is equal to or better than non-treated 316 stainless steel. The increase in corrosion resistance to pitting and stress corrosion is very pronounced in media which contain chlorides (e.g. sea water, bleach, HCl, etc.). The Ty-Cor™ process applied to the rear ferrule also helps eliminate galling and ensures proper sealing on tube end make ups.



## ABS Certification



Tylok has received the Certificate of Type Approval from the American Bureau of Shipping (ABS). The following Part Families are ABS approved: DFC – Female Connector, DMC – Male Connector, DU – Union, DELU – Union Elbow, DME – Male Elbow and DTTT – Union Tee. For further information visit [www.eagle.org](http://www.eagle.org).

## Features

- Double ferrule swaging action
- Total component interchangeability
- Heat Code traceable
- ASTM material construction
- Corrosion resistant 316 Stainless Steel rear ferrules

## Quality Management System

QMI has registered Tylok International's Quality Management System to ISO 9001:2000. The quality system complies with the international standard ISO 9001:2000 and its technical equivalent, ANSI/ISO/ASQ Q9001:2000. Tylok strives to continuously improve the effectiveness of the Quality Management System by each member within the organization.



ISO 9001:2000  
Certificate No.012106

# Table of Contents/Product Locator

**HOW TO ORDER**

*How To Order*

4



**DATANF**

*Adapter Tube to AN Flare*

5



**DATPF**

*Adapter Tube to Female Pipe*


6



**DATPM**

*Adapter Tube to Male Pipe*


7



**DBHA**

*Bulkhead Adapter*


8



**DBHFP**


*Bulkhead Female Pipe Connector*

9



**DBHMP**  
*Bulkhead Male Pipe Connector*

10



**DBHU**  
*Bulkhead Union*

11




**DBUANF**  
*Bulkhead to AN Flare Union*

11



**DCAP**  
*Cap*

12




**DF PLUG**  
*Fitting Plug*

12



**DFC**  
*Female Connector*

13



**DMC**  
*Male Connector*

14 & 15



**DMC-ORS**  
*O-Ring Straight Thread Male Conn.*

16



**DMC-ORT**  
*O-Ring Pipe Thread Male Conn.*

17



**DPCU**  
*Port Connector Union*

18



**DRATT**  
*Reducer Adapter Tube to Tube*

19



**DRPC**  
*Reducing Port Connector*

20



**DRU**  
*Reducing Union*

21



**DTBW**  
*Tube to Butt Weld Connector*

22



**DTSW**  
*Tube to Socket Weld Connector*

23




**DU**  
*Union*

24



**DUANF**  
*Tube to AN Flare Union*


25



**DELU**  
*Union Elbow*


26

# Table of Contents/Product Locator




**DFE**  
Female Elbow

27




**DME**  
Male Elbow

28 & 29




**DTBWE**  
Tube to Butt  
Weld Elbow

30




**DTSWE**  
Tube to  
Socket Weld  
Elbow

31




**DTFT**  
Female Run  
Tee

32




**DTMT**  
Male Run  
Tee

33




**DTTF**  
Female  
Branch Tee

34




**DTTM**  
Male  
Branch Tee

35




**DTTT**  
Union Tee

36




**DCR**  
Union Cross

37



**DBI**  
Barbed  
Insert

38




**DPI**  
Plane  
Insert

39



**DN**  
Nut

40



**DKN**  
Knurled Nut

40



**DFC**  
Front Collet  
(Ferrule)

41



**DRC**  
Rear Collet  
(Ferrule)

41

**COMPONENT  
REPLACEMENT  
PARTS**

Replacement  
Parts

41

**SPECIAL  
PRODUCTS**

Special  
Products

42

**CBC-LOK®  
INSTALLATION  
INSTRUCTIONS**

Installation  
Instructions

43

**CBC-LOK® TUBING  
SELECTION &  
PREPARATION**

Tubing  
Selection &  
Preparation

44

**GAS SERVICE/  
SAFETY/  
QUALITY**

Gas Service/  
Safety/  
Quality

45

**TECHNICAL  
DATA**

Technical  
Data  
Pre-Set Tool

46

**TRACEABILITY/  
MATERIAL SPEC./  
PRE-SET TOOL**

Heat  
Traceability/  
Mat'l Spec./  
Pre-Set Tool


47

**TUBE INSERTION  
CHART/  
APPLICATIONS**


Tube Insertion  
Chart/  
Applications

48







## Adapter Tube to AN Flare



PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	J THREAD	A	D	E THRU HOLE	L	BH BODY HEX
2-DATANF-2	2-TA-1-2AN	1/8	5/16-24	1.203	.448	.062	.531	3/8
2-DATANF-4	2-TA-1-4AN	1/8	7/16-20	1.312	.550	.094	.531	1/2
3-DATANF-3	3-TA-1-3AN	3/16	3/8-24	1.250	.479	.125	.562	7/16
4-DATANF-4	4-TA-1-4AN	1/4	7/16-20	1.469	.550	.172	.625	1/2
5-DATANF-5	5-TA-1-5AN	5/16	1/2-20	1.453	.550	.234	.656	9/16
6-DATANF-4	6-TA-1-4AN	3/8	7/16-20	1.531	.550	.172	.687	1/2
6-DATANF-6	6-TA-1-6AN	3/8	9/16-18	1.500	.556	.281	.687	5/8
8-DATANF-8	8-TA-1-8AN	1/2	3/4-16	1.906	.657	.391	.906	13/16
10-DATANF-10	10-TA-1-10AN	5/8	7/8-14	2.031	.758	.484	.969	15/16
12-DATANF-12	12-TA-1-12AN	3/4	1-1/16-12	2.187	.864	.656	.969	1-1/8
16-DATANF-16	16-TA-1-16AN	1	1-5/16-12	2.531	.911	.937	1.219	1-3/8


\*NOTE: All dimensions subject to change, to be used for reference only.

## Adapter Tube to Female Pipe




PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	P PIPE END NPT	A	E THRU HOLE	L	BH BODY HEX
2-DATPF-2	2-TA-7-2      2FA2N	1/8	1/8	1.234	.094	.531	9/16
2-DATPF-4	2-TA-7-4      2FA4N	1/8	1/4	1.375	.094	.531	3/4
3-DATPF-2	3-TA-7-2      3FA2N	3/16	1/8	1.266	.125	.562	9/16
3-DATPF-4	3-TA-7-4      3FA4N	3/16	1/4	1.406	.125	.562	3/4
4-DATPF-2	4-TA-7-2      4FA2N	1/4	1/8	1.312	.187	.625	9/16
4-DATPF-4	4-TA-7-4      4FA4N	1/4	1/4	1.469	.187	.625	3/4
4-DATPF-6	4-TA-7-6      4FA6N	1/4	3/8	1.562	.187	.625	7/8
4-DATPF-8	4-TA-7-8      4FA8N	1/4	1/2	1.812	.187	.625	1-1/16
5-DATPF-2	5-TA-7-2      5FA2N	5/16	1/8	1.359	.250	.656	9/16
5-DATPF-4	5-TA-7-4      5FA4N	5/16	1/4	1.516	.250	.656	3/4
6-DATPF-2	6-TA-7-2      6FA2N	3/8	1/8	1.391	.281	.687	9/16
6-DATPF-4	6-TA-7-4      6FA4N	3/8	1/4	1.547	.281	.687	3/4
6-DATPF-6	6-TA-7-6      6FA6N	3/8	3/8	1.625	.281	.687	7/8
6-DATPF-8	6-TA-7-8      6FA8N	3/8	1/2	1.843	.281	.687	1-1/16
8-DATPF-4	8-TA-7-4      8FA4N	1/2	1/4	1.719	.391	.906	3/4
8-DATPF-6	8-TA-7-6      8FA6N	1/2	3/8	1.859	.391	.906	7/8
8-DATPF-8	8-TA-7-8      8FA8N	1/2	1/2	2.093	.391	.906	1-1/16
10-DATPF-6	10-TA-7-6     10FA6N	5/8	3/8	1.828	.500	.969	7/8
10-DATPF-8	10-TA-7-8     10FA8N	5/8	1/2	2.093	.500	.969	1-1/16
12-DATPF-8	12-TA-7-8     12FA8N	3/4	1/2	2.093	.594	.969	1-1/16
14-DATPF-12	14-TA-7-12    14FA12N	7/8	3/4	2.203	.687	1.031	1-1/4
16-DATPF-12	16-TA-7-12    16FA12N	1	3/4	2.406	.797	1.219	1-1/4
16-DATPF-16	16-TA-7-16    16FA16N	1	1	2.547	.797	1.219	1-5/8

\*NOTE: All dimensions subject to change, to be used for reference only.



## Adapter Tube to Male Pipe





PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	P PIPE END NPT	A	D	E <sup>1</sup> THRU HOLE	L	W	BH BODY HEX
2-DATPM-2	2-TA-1-2 2MA2N	1/8	1/8	1.156	.375	.093	.531	.022	7/16
2-DATPM-4	2-TA-1-4 2MA4N	1/8	1/4	1.375	.562	.093	.531	.022	9/16
3-DATPM-2	3-TA-1-2 3MA2N	3/16	1/8	1.187	.375	.187	.562	.022	7/16
3-DATPM-4	3-TA-1-4 3MA4N	3/16	1/4	1.406	.562	.281	.562	.022	9/16
4-DATPM-2	4-TA-1-2 4MA2N	1/4	1/8	1.250	.375	.171	.625	.032	7/16
4-DATPM-4	4-TA-1-4 4MA4N	1/4	1/4	1.469	.562	.171	.625	.032	9/16
4-DATPM-6	4-TA-1-6 4MA6N	1/4	3/8	1.500	.562	.171	.625	.032	11/16
4-DATPM-8	4-TA-1-8 4MA8N	1/4	1/2	1.718	.750	.171	.625	.032	7/8
5-DATPM-2	5-TA-1-2 5MA2N	5/16	1/8	1.297	.375	.187	.656	.032	7/16
5-DATPM-4	5-TA-1-4 5MA4N	5/16	1/4	1.500	.562	.250	.656	.032	9/16
6-DATPM-2	6-TA-1-2 6MA2N	3/8	1/8	1.343	.375	.187	.687	.032	7/16
6-DATPM-4	6-TA-1-4 6MA4N	3/8	1/4	1.547	.562	.281	.687	.032	9/16
6-DATPM-6	6-TA-1-6 6MA6N	3/8	3/8	1.562	.562	.281	.687	.032	11/16
6-DATPM-8	6-TA-1-8 6MA8N	3/8	1/2	1.781	.750	.281	.687	.032	7/8
8-DATPM-4	8-TA-1-4 8MA4N	1/2	1/4	1.750	.562	.281	.906	.047	9/16
8-DATPM-6	8-TA-1-6 8MA6N	1/2	3/8	1.781	.562	.375	.906	.047	11/16
8-DATPM-8	8-TA-1-8 8MA8N	1/2	1/2	2.000	.750	.391	.906	.047	7/8
10-DATPM-6	10-TA-1-6 10MA6N	5/8	3/8	1.844	.562	.375	.969	.047	11/16
10-DATPM-8	10-TA-1-8 10MA8N	5/8	1/2	2.062	.750	.468	.969	.047	7/8
10-DATPM-12	10-TA-1-12 10MA12N	5/8	3/4	2.062	.750	.500	.969	.047	1-1/16
12-DATPM-8	12-TA-1-8 12MA8N	3/4	1/2	2.062	.750	.468	.969	.047	7/8
12-DATPM-12	12-TA-1-12 12MA12N	3/4	3/4	2.062	.750	.594	.969	.047	1-1/16
12-DATPM-16	12-TA-1-16 12MA16N	3/4	1	2.359	.937	.594	.969	.047	1-3/8
14-DATPM-12	14-TA-1-12 14MA12N	7/8	3/4	2.125	.750	.687	1.031	.047	1-3/8
16-DATPM-12	16-TA-1-12 16MA12N	1	3/4	2.312	.750	.625	1.218	.047	1-1/16
16-DATPM-16	16-TA-1-16 16MA16N	1	1	2.625	.937	.797	1.218	.047	1-3/8

\*NOTE: All dimensions subject to change, to be used for reference only.


<sup>1</sup> The E dimension is the minimum opening. These fittings may have a larger opening at the pipe/straight thread end.

## Bulkhead Adapter




PART NUMBER	INTERCHANGES WITH	T1 TUBE O.D.	T2 TUBE O.D.	A	B	C	D	E THRU HOLE	F	L	NH NUT HEX	JNH JAM NUT HEX	BH BODY HEX	PANEL HOLE	
2-DBHA-2	200-R1-2	2TUBC2	1/8	1/8	1.953	.500	1.234	.531	.078	.969	1.687	7/16	1/2	1/2	21/64
4-DBHA-4	400-R1-4	4TUBC4	1/4	1/4	2.203	.609	1.328	.625	.187	1.031	1.906	9/16	5/8	5/8	29/64
6-DBHA-6	600-R1-6	6TUBC6	3/8	3/8	2.406	.656	1.453	.687	.281	1.156	2.125	11/16	3/4	3/4	37/64
8-DBHA-8	810-R1-8	8TUBC8	1/2	1/2	2.875	.906	1.656	.906	.391	1.250	2.468	7/8	15/16	15/16	49/64

\*NOTE: All dimensions subject to change, to be used for reference only.





## Bulkhead Female Pipe Connector



PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	P PIPE END NPT	A	B	C	D	E THRU HOLE	L	NH NUT HEX	JNH JAM NUT HEX	BH BODY HEX	PANEL HOLE
2-DBHFP-2	200-71-2 2FBC2N	1/8	1/8	1.766	.500	1.234	.969	.094	1.500	7/16	1/2	9/16	21/64
3-DBHFP-2	300-71-2 3FBC2N	3/16	1/8	1.797	.547	1.266	1.000	.125	1.531	1/2	9/16	9/16	25/64
4-DBHFP-2	400-71-2 4FBC2N	1/4	1/8	1.859	.609	1.328	1.031	.187	1.562	9/16	5/8	5/8	29/64
4-DBHFP-4	400-71-4 4FBC4N	1/4	1/4	2.047	.609	1.328	1.031	.187	1.750	9/16	5/8	3/4	29/64
5-DBHFP-2	500-71-2 5FBC2N	5/16	1/8	1.969	.641	1.422	1.125	.250	1.656	5/8	3/4	11/16	33/64
6-DBHFP-4	600-71-4 6FBC4N	3/8	1/4	2.172	.656	1.453	1.156	.281	1.875	11/16	3/4	3/4	37/64
8-DBHFP-6	810-71-6 8FBC6N	1/2	3/8	2.437	.906	1.656	1.250	.406	2.031	7/8	15/16	15/16	49/64
8-DBHFP-8	810-71-8 8FBC8N	1/2	1/2	2.625	.906	1.656	1.250	.406	2.219	7/8	15/16	1-1/16	49/64
10-DBHFP-8	1010-71-8 10FBC8N	5/8	1/2	2.656	.969	1.687	1.281	.500	2.250	1	1-1/16	1-1/16	57/64
16-DBHFP-16	1610-71-16 16FBC16N	1	1	3.687	1.234	2.266	1.781	.875	3.187	1-1/2	1-1/2	1-5/8	1-21/64

\*NOTE: All dimensions subject to change, to be used for reference only.


## Bulkhead Male Pipe Connector




PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	P PIPE END NPT	A	B	C	D	E <sup>1</sup> THRU HOLE	F	L	NH NUT HEX	JNH JAM NUT HEX	BH BODY HEX	PANEL HOLE
1-DBHMP-1	100-11-1 1MBC1N	1/16	1/16	1.187	.437	.687	.375	.052	.531	1.031	5/16	7/16	5/16	13/64
1-DBHMP-2	100-11-2 1MBC2N	1/16	1/8	1.234	.437	.687	.375	.052	.531	1.094	5/16	7/16	7/16	13/64
2-DBHMP-2	200-11-2 2MBC2N	1/8	1/8	1.828	.500	1.234	.375	.094	.969	1.578	7/16	1/2	1/2	21/64
3-DBHMP-2	300-11-2 3MBC2N	3/16	1/8	1.859	.547	1.266	.375	.125	1.000	1.594	1/2	9/16	9/16	25/64
4-DBHMP-2	400-11-2 4MBC2N	1/4	1/8	1.953	.609	1.328	.375	.187	1.031	1.656	9/16	5/8	5/8	29/64
4-DBHMP-4	400-11-4 4MBC4N	1/4	1/4	2.109	.609	1.328	.562	.187	1.031	1.843	9/16	5/8	5/8	29/64
4-DBHMP-6	400-11-6 4MBC6N	1/4	3/8	2.187	.609	1.328	.562	.187	1.016	1.891	9/16	5/8	11/16	29/64
4-DBHMP-8	400-11-8 4MBC8N	1/4	1/2	2.484	.609	1.328	.562	.187	1.016	2.187	9/16	5/8	7/8	29/64
6-DBHMP-4	600-11-4 6MBC4N	3/8	1/4	2.266	.656	1.453	.562	.281	1.156	1.969	11/16	3/4	3/4	37/64
6-DBHMP-6	600-11-6 6MBC6N	3/8	3/8	2.312	.656	1.437	.562	.281	1.156	1.969	11/16	3/4	3/4	37/64
6-DBHMP-8	600-11-8 6MBC8N	3/8	1/2	2.609	.656	1.437	.750	.375	1.156	2.312	11/16	3/4	7/8	37/64
8-DBHMP-4	810-11-4 8MBC4N	1/2	1/4	2.547	.906	1.656	.562	.375	1.250	2.141	7/8	15/16	15/16	49/64
8-DBHMP-6	810-11-6 8MBC6N	1/2	3/8	2.484	.906	1.656	.562	.375	1.250	2.094	7/8	15/16	15/16	49/64
8-DBHMP-8	810-11-8 8MBC8N	1/2	1/2	2.719	.906	1.656	.750	.406	1.250	2.312	7/8	15/16	15/16	49/64

\*NOTE: All dimensions subject to change, to be used for reference only.

<sup>1</sup> The E dimension is the minimum opening. These fittings may have a larger opening at the pipe/straight thread end.




## Bulkhead Union




PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	A	B	C1	C2	D	E THRU HOLE	L	NH NUT HEX	JNH JAM NUT HEX	BH BODY HEX	PANEL HOLE HEX
1-DBHU-1	100-61 1BC1	1/16	1.234	.344	.687	.437	.531	.052	.937	5/16	5/16	5/16	13/64
2-DBHU-2	200-61 2BC2	1/8	2.016	.500	1.234	.609	.969	.094	1.500	7/16	1/2	1/2	21/64
3-DBHU-3	300-61 3BC3	3/16	2.109	.547	1.266	.625	1.000	.125	1.594	1/2	9/16	9/16	25/64
4-DBHU-4	400-61 4BC4	1/4	2.266	.609	1.328	.703	1.031	.187	1.687	9/16	5/8	5/8	29/64
5-DBHU-5	500-61 5BC5	5/16	2.391	.641	1.406	.734	1.125	.250	1.812	5/8	11/16	11/16	33/64
6-DBHU-6	600-61 6BC6	3/8	2.453	.656	1.453	.766	1.156	.281	1.875	11/16	3/4	3/4	37/64
8-DBHU-8	810-61 8BC8	1/2	2.797	.906	1.656	.859	1.250	.406	2.000	7/8	15/16	15/16	49/64
10-DBHU-10	1010-61 10BC10	5/8	2.859	.969	1.687	.859	1.281	.500	2.062	1	1-1/16	1-1/16	57/64
12-DBHU-12	1210-61 12BC12	3/4	3.109	.969	1.875	.859	1.469	.625	2.312	1-1/8	1-3/16	1-3/16	1-1/64
14-DBHU-14	1410-61 14BC14	7/8	3.328	1.031	2.094	.875	1.687	.718	2.531	1-1/4	1-3/8	1-3/8	1-9/64
16-DBHU-16	1610-61 16BC16	1	3.766	1.234	2.266	1.047	1.781	.875	2.812	1-1/2	1-5/8	1-5/8	1-21/64

\*NOTE: All dimensions subject to change, to be used for reference only.



## Bulkhead to AN Flare Union





PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	J THREAD	A	B	C	D	E THRU HOLE	L	NH NUT HEX	BH BODY HEX	JNH JAM NUT HEX	PANEL HOLE HEX
2-DBUANF-2	200-61-2AN 2XABC2	1/8	5/16-24	1.906	.516	1.234	.453	.062	.969	7/16	1/2	1/2	21/64
3-DBUANF-3	300-61-3AN 3XABC3	3/16	3/8-24	1.984	.547	1.266	.484	.125	1.000	1.719	1/2	9/16	25/64
4-DBUANF-4	400-61-4AN 4XABC4	1/4	7/16-20	2.125	.609	1.328	.547	.172	1.031	1.828	9/16	5/8	29/64
5-DBUANF-5	500-61-5AN 5XABC5	5/16	1/2-20	2.219	.641	1.406	.547	.234	1.125	1.922	5/8	11/16	33/64
6-DBUANF-6	600-61-6AN 6XABC6	3/8	9/16-18	2.250	.656	1.453	.562	.281	1.156	1.969	11/16	11/16	37/64
8-DBUANF-8	810-61-8AN 8XABC8	1/2	3/4-16	2.594	.906	1.656	.656	.391	1.250	2.187	7/8	15/16	49/64
10-DBUANF-10	1010-61-10AN 10XABC10	5/8	7/8-14	2.734	.969	1.687	.766	.484	1.281	2.234	1	1-1/16	57/64
12-DBUANF-12	1210-61-12AN 12XABC12	3/4	1-1/16-12	3.109	.969	1.875	.859	.609	1.469	2.719	1-1/8	1-3/16	1-1/64
16-DBUANF-16	1610-61-16AN 16XABC16	1	1-5/16-12	3.641	1.234	2.266	.906	.844	1.781	3.156	1-1/2	1-5/8	1-21/64

\*NOTE: All dimensions subject to change, to be used for reference only.

# DCAP/DF Plug



## Cap



PART NUMBER	INTERCHANGES WITH		T TUBE O.D.	A	B	C	L	BH BODY HEX	NH NUT HEX
1-DCAP	100-C	1BLEN1	1/16	.594	.344	.437	.437	5/16	5/16
2-DCAP	200-C	2BLEN2	1/8	.797	.500	.609	.531	7/16	7/16
3-DCAP	300-C	3BLEN3	3/16	.844	.547	.625	.578	7/16	1/2
4-DCAP	400-C	4BLEN4	1/4	.922	.609	.703	.625	1/2	9/16
5-DCAP	500-C	5BLEN5	5/16	.969	.641	.734	.672	9/16	5/8
6-DCAP	600-C	6BLEN6	3/8	1.016	.656	.766	.719	5/8	11/16
8-DCAP	810-C	8BLEN8	1/2	1.156	.906	.859	.750	13/16	7/8
10-DCAP	1010-C	10BLEN10	5/8	1.188	.969	.859	.781	15/16	1
12-DCAP	1210-C	12BLEN12	3/4	1.234	.969	.859	.844	1-1/16	1-1/8
14-DCAP	1410-C	14BLEN14	7/8	1.344	1.016	.859	.937	1-3/16	1-1/4
16-DCAP	1610-C	16BLEN16	1	1.516	1.234	1.047	1.031	1-3/8	1-1/2


\*NOTE: All dimensions subject to change, to be used for reference only.

## Fitting Plug




PART NUMBER	INTERCHANGES WITH		T TUBE O.D.	NH NUT HEX
1-DF PLUG	100-P	1BLP1	1/16	5/16
2-DF PLUG	200-P	2BLP2	1/8	7/16
3-DF PLUG	300-P	3BLP3	3/16	1/2
4-DF PLUG	400-P	4BLP4	1/4	9/16
5-DF PLUG	500-P	5BLP5	5/16	5/8
6-DF PLUG	600-P	6BLP6	3/8	11/16
8-DF PLUG	810-P	8BLP8	1/2	7/8
10-DF PLUG	1010-P	10BLP10	5/8	1
12-DF PLUG	1210-P	12BLP12	3/4	1-1/8
14-DF PLUG	1410-P	14BLP14	7/8	1-1/4
16-DF PLUG	1610-P	16BLP16	1	1-1/2

\*NOTE: All dimensions subject to change, to be used for reference only.




## Female Connector



PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	P PIPE END NPT	A	B	C	E THRU HOLE	L	NH NUT HEX	BH BODY HEX
1-DFC-1	100-7-1	1FSC1N	1/16	.937	.344	.437	.052	.782	5/16	7/16
1-DFC-2	100-7-2	1FSC2N	1/16	.969	.344	.437	.052	.812	5/16	9/16
2-DFC-2	200-7-2	2FSC2N	1/8	1.125	.500	.609	.094	.875	7/16	9/16
2-DFC-4	200-7-4	2FSC4N	1/8	1.328	.500	.609	.094	1.062	7/16	3/4
2-DFC-6	200-7-6	2FSC6N	1/8	1.390	.500	.609	.094	1.125	7/16	7/8
3-DFC-2	300-7-2	3FSC2N	3/16	1.171	.547	.625	.125	.906	1/2	9/16
3-DFC-4	300-7-4	3FSC4N	3/16	1.344	.547	.625	.125	1.094	1/2	3/4
3-DFC-8	300-7-8	3FSC8N	3/16	1.594	.547	.625	.125	1.344	1/2	1-1/8
4-DFC-1	400-7-1	4FSC1N	1/4	1.203	.609	.703	.187	.906	9/16	1/2
4-DFC-2	400-7-2	4FSC2N	1/4	1.234	.609	.703	.187	.937	9/16	9/16
4-DFC-4	400-7-4	4FSC4N	1/4	1.406	.609	.703	.187	1.125	9/16	3/4
4-DFC-6	400-7-6	4FSC6N	1/4	1.484	.609	.703	.187	1.187	9/16	7/8
4-DFC-8	400-7-8	4FSC8N	1/4	1.670	.609	.703	.187	1.375	9/16	1-1/16
5-DFC-2	500-7-2	5FSC2N	5/16	1.266	.640	.734	.250	.969	5/8	9/16
5-DFC-4	500-7-4	5FSC4N	5/16	1.453	.640	.734	.250	1.156	5/8	3/4
5-DFC-6	500-7-6	5FSC6N	5/16	1.515	.640	.734	.250	1.218	5/8	7/8
5-DFC-8	500-7-8	5FSC8N	5/16	1.703	.640	.734	.250	1.406	5/8	1-1/16
6-DFC-2	600-7-2	6FSC2N	3/8	1.297	.656	.766	.281	1.000	11/16	5/8
6-DFC-4	600-7-4	6FSC4N	3/8	1.484	.656	.766	.281	1.187	11/16	3/4
6-DFC-6	600-7-6	6FSC6N	3/8	1.547	.656	.766	.281	1.250	11/16	7/8
6-DFC-8	600-7-8	6FSC8N	3/8	1.734	.656	.766	.281	1.437	11/16	1-1/16
6-DFC-12	600-7-12	6FSC12N	3/8	1.875	.656	.766	.281	1.593	11/16	1-1/4
8-DFC-4	810-7-4	8FSC4N	1/2	1.593	.906	.859	.406	1.187	7/8	13/16
8-DFC-6	810-7-6	8FSC6N	1/2	1.656	.906	.859	.406	1.250	7/8	7/8
8-DFC-8	810-7-8	8FSC8N	1/2	1.843	.906	.859	.406	1.437	7/8	1-1/16
8-DFC-12	810-7-12	8FSC12N	1/2	1.906	.906	.859	.406	1.500	7/8	1-1/4
8-DFC-16	810-7-16	8FSC16N	1/2	2.265	.906	.859	.406	1.875	7/8	1-5/8
10-DFC-4	1010-7-4	10FSC4N	5/8	1.797	.969	.859	.281	1.406	1	15/16
10-DFC-6	1010-7-6	10FSC6N	5/8	1.656	.969	.859	.500	1.250	1	15/16
10-DFC-8	1010-7-8	10FSC8N	5/8	1.844	.969	.859	.500	1.437	1	1-1/16
10-DFC-12	1010-7-12	10FSC12N	5/8	1.953	.969	.859	.500	1.562	1	1-1/4
12-DFC-6	1210-7-6	12FSC6N	3/4	1.655	.969	.859	.500	1.265	1-1/8	1-1/16
12-DFC-8	1210-7-8	12FSC8N	3/4	1.844	.969	.859	.625	1.437	1-1/8	1-1/16
12-DFC-12	1210-7-12	12FSC12N	3/4	1.906	.969	.859	.625	1.500	1-1/8	1-1/4
12-DFC-16	1210-7-16	12FSC16N	3/4	2.265	.969	.859	.625	1.875	1-1/8	1-5/8
14-DFC-8	1410-7-8	14FSC8N	7/8	1.828	1.016	.859	.687	1.437	1-1/4	1-5/16
14-DFC-12	1410-7-12	14FSC12N	7/8	1.969	1.016	.859	.719	1.562	1-1/4	1-3/8
14-DFC-16	1410-7-16	14FSC16N	7/8	2.234	1.016	.859	.719	1.843	1-1/4	1-5/8
16-DFC-12	1610-7-12	16FSC12N	1	2.109	1.234	1.047	.875	1.625	1-1/2	1-3/8
16-DFC-16	1610-7-16	16FSC16N	1	2.453	1.234	1.047	.875	1.969	1-1/2	1-5/8

\*NOTE: All dimensions subject to change, to be used for reference only.



## Male Connector



PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	P PIPE END NPT	A	B	C	D	E <sup>1</sup> THRU HOLE	L	NH NUT HEX	BH BODY HEX	
1-DMC-1	100-1-1	1MSC1N	1/16	1/16	.937	.344	.437	.375	.052	.797	5/16	5/16
1-DMC-2	100-1-2	1MSC2N	1/16	1/8	1.031	.344	.437	.375	.052	.875	5/16	7/16
2-DMC-1	200-1-1	2MSC1N	1/8	1/16	1.172	.500	.609	.375	.094	.906	7/16	7/16
2-DMC-2	200-1-2	2MSC2N	1/8	1/8	1.203	.500	.609	.375	.094	.937	7/16	7/16
2-DMC-4	200-1-4	2MSC4N	1/8	1/4	1.406	.500	.609	.562	.094	1.140	7/16	9/16
2-DMC-6	200-1-6	2MSC6N	1/8	3/8	1.406	.500	.609	.562	.094	1.156	7/16	11/16
2-DMC-8	200-1-8	2MSC8N	1/8	1/2	1.656	.500	.609	.750	.094	1.406	7/16	7/8
3-DMC-2	300-1-2	3MSC2N	3/16	1/8	1.234	.546	.625	.375	.125	.969	1/2	7/16
3-DMC-4	300-1-4	3MSC4N	3/16	1/4	1.437	.546	.625	.562	.125	1.171	1/2	9/16
4-DMC-1	400-1-1	4MSC1N	1/4	1/16	1.299	.609	.703	.375	.125	1.000	9/16	1/2
4-DMC-2	400-1-2	4MSC2N	1/4	1/8	1.299	.609	.703	.375	.187	1.000	9/16	1/2
4-DMC-4	400-1-4	4MSC4N	1/4	1/4	1.484	.609	.703	.562	.187	1.203	9/16	9/16
4-DMC-6	400-1-6	4MSC6N	1/4	3/8	1.516	.609	.703	.562	.187	1.219	9/16	11/16
4-DMC-8	400-1-8	4MSC8N	1/4	1/2	1.766	.609	.703	.750	.187	1.469	9/16	7/8
4-DMC-12	400-1-12	4MSC12N	1/4	3/4	1.828	.609	.703	.750	.187	1.531	9/16	1-1/16
4-DMC-16	400-1-16	4MSC16N	1/4	1	2.109	.609	.703	.937	.187	1.812	9/16	1-3/8
5-DMC-2	500-1-2	5MSC2N	5/16	1/8	1.343	.641	.734	.375	.187	1.047	5/8	9/16
5-DMC-4	500-1-4	5MSC4N	5/16	1/4	1.516	.641	.734	.562	.250	1.234	5/8	9/16
5-DMC-6	500-1-6	5MSC6N	5/16	3/8	1.547	.641	.734	.562	.250	1.250	5/8	11/16
5-DMC-8	500-1-8	5MSC8N	5/16	1/2	1.765	.641	.734	.750	.250	1.468	5/8	7/8
6-DMC-2	600-1-2	6MSC2N	3/8	1/8	1.390	.656	.766	.375	.187	1.109	11/16	5/8
6-DMC-4	600-1-4	6MSC4N	3/8	1/4	1.578	.656	.766	.562	.281	1.281	11/16	5/8
6-DMC-6	600-1-6	6MSC6N	3/8	3/8	1.578	.656	.766	.562	.281	1.281	11/16	11/16
6-DMC-8	600-1-8	6MSC8N	3/8	1/2	1.828	.656	.766	.750	.281	1.531	11/16	7/8
6-DMC-12	600-1-12	6MSC12N	3/8	3/4	1.875	.656	.766	.750	.281	1.593	11/16	1-1/16
6-DMC-16	600-1-16	6MSC16N	3/8	1	2.141	.656	.766	.937	.281	1.843	11/16	1-3/8

\*NOTE: All dimensions subject to change, to be used for reference only.

<sup>1</sup> The E dimension is the minimum opening. These fittings may have a larger opening at the pipe/straight thread end.





PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	P PIPE END NPT	A	B	C	D	E <sup>1</sup> THRU HOLE	L	NH NUT HEX	BH BODY HEX	
8-DMC-2	810-1-2	8MSC2N	1/2	1/8	1.531	.906	.859	.375	.187	1.125	7/8	13/16
8-DMC-4	810-1-4	8MSC4N	1/2	1/4	1.719	.906	.859	.562	.281	1.312	7/8	13/16
8-DMC-6	810-1-6	8MSC6N	1/2	3/8	1.719	.906	.859	.562	.375	1.312	7/8	13/16
8-DMC-8	810-1-8	8MSC8N	1/2	1/2	1.937	.906	.859	.750	.406	1.531	7/8	7/8
8-DMC-12	810-1-12	8MSC12N	1/2	3/4	1.984	.906	.859	.750	.406	1.593	7/8	1-1/16
8-DMC-16	810-1-16	8MSC16N	1/2	1	2.250	.906	.859	.937	.406	1.859	7/8	1-3/8
10-DMC-4	1010-1-4	10MSC4N	5/8	1/4	1.934	.969	.859	.562	.281	1.343	1	15/16
10-DMC-6	1010-1-6	10MSC6N	5/8	3/8	1.934	.969	.859	.562	.375	1.343	1	15/16
10-DMC-8	1010-1-8	10MSC8N	5/8	1/2	1.937	.969	.859	.750	.469	1.531	1	15/16
10-DMC-12	1010-1-12	10MSC12N	5/8	3/4	1.984	.969	.859	.750	.500	1.593	1	1-1/16
10-DMC-16	1010-1-16	10MSC16N	5/8	1	2.172	.969	.859	.937	.500	1.781	1	1-3/8
12-DMC-4	1210-1-4	12MSC4N	3/4	1/4	1.796	.969	.859	.562	.281	1.405	1-1/4	1-1/8
12-DMC-6	1210-1-6	12MSC6N	3/4	3/8	1.796	.969	.859	.562	.375	1.405	1-1/4	1-1/8
12-DMC-8	1210-1-8	12MSC8N	3/4	1/2	1.984	.969	.859	.750	.468	1.593	1-1/8	1-1/16
12-DMC-12	1210-1-12	12MSC12N	3/4	3/4	1.984	.969	.859	.750	.625	1.593	1-1/8	1-1/16
12-DMC-16	1210-1-16	12MSC16N	3/4	1	2.250	.969	.859	.937	.625	1.859	1-1/8	1-3/8
14-DMC-8	1410-1-8	14MSC8N	7/8	1/2	1.984	1.015	.859	.750	.468	1.593	1-3/8	1-1/4
14-DMC-12	1410-1-12	14MSC12N	7/8	3/4	1.984	1.015	.859	.750	.625	1.593	1-1/4	1-3/16
14-DMC-16	1410-1-16	14MSC16N	7/8	1	2.250	1.015	.859	.937	.718	1.859	1-1/4	1-3/8
16-DMC-4	1610-1-4	16MSC4N	1	1/4	2.055	1.234	1.046	.562	.281	1.562	1-1/2	1-3/8
16-DMC-6	1610-1-6	16MSC6N	1	3/8	2.055	1.234	1.046	.562	.375	1.562	1-1/2	1-3/8
16-DMC-8	1610-1-8	16MSC8N	1	1/2	2.265	1.234	1.046	.750	.468	1.781	1-1/2	1-3/8
16-DMC-12	1610-1-12	16MSC12N	1	3/4	2.265	1.234	1.046	.750	.625	1.781	1-1/2	1-3/8
16-DMC-16	1610-1-16	16MSC16N	1	1	2.453	1.234	1.046	.937	.875	1.969	1-1/2	1-3/8

\*NOTE: All dimensions subject to change, to be used for reference only.

<sup>1</sup> The E dimension is the minimum opening. These fittings may have a larger opening at the pipe/straight thread end.

## O-Ring Straight Thread Male Connector




PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	J THREAD	A	B	C	D	E <sup>1</sup> THRU HOLE	L	NH NUT HEX	BH BODY HEX	O-RING
1-DMC-ORS	100-1-OR 1M2SC1	1/16	5/16-24	1.047	.344	.437	.343	.047	.906	5/16	9/16	AS-011
2-DMC-ORS	200-1-OR 2M2SC2	1/8	5/16-24	1.297	.500	.609	.343	.094	1.031	7/16	9/16	AS-011
3-DMC-ORS	300-1-OR 3M2SC3	3/16	3/8-24	1.359	.547	.625	.375	.125	1.094	1/2	5/8	AS-012
4-DMC-ORS	400-1-OR 4M2SC4	1/4	7/16-20	1.516	.609	.703	.406	.187	1.219	9/16	3/4	AS-111
5-DMC-ORS	500-1-OR 5M2SC5	5/16	1/2-20	1.609	.641	.734	.437	.250	1.312	5/8	7/8	AS-112
6-DMC-ORS	600-1-OR 6M2SC6	3/8	9/16-18	1.672	.656	.766	.468	.281	1.375	11/16	15/16	AS-113
8-DMC-ORS	810-1-OR 8M2SC8	1/2	3/4-16	1.812	.906	.859	.468	.406	1.406	7/8	1-1/8	AS-116
12-DMC-ORS	1210-1-OR 12M2SC12	3/4	1-1/16-12	2.062	.969	.859	.562	.625	1.656	1-1/8	1-1/2	AS-215
16-DMC-ORS	1610-1-OR 16M2SC16	1	1-5/16-12	2.297	1.234	1.047	.562	.875	1.812	1-1/2	1-3/4	AS-219


\*NOTE: All dimensions subject to change, to be used for reference only.

\*\*NOTE: Stainless steel and carbon steel O-seal fittings up to 1 in. are rated to 3000 psi.

<sup>1</sup> The E dimension is the minimum opening. These fittings may have a larger opening at the pipe/straight thread end.



## O-Ring Pipe Thread Male Connector





PART NUMBER	INTERCHANGES WITH		T TUBE O.D.	P PIPE END NPT	A	B	C	D	E <sup>1</sup> THRU HOLE	L	NH NUT HEX	BH BODY HEX	O-RING
2-DMC-2-ORT	200-1-2-OR	2M3SC2	1/8	1/8	1.297	.500	.609	.280	.094	1.031	7/16	3/4	AS-111
2-DMC-4-ORT	200-1-4-OR	2M3SC4	1/8	1/4	1.437	.516	.609	.375	.094	1.172	7/16	15/16	AS-113
3-DMC-4-ORT	300-1-4-OR	3M3SC4	3/16	1/4	1.469	.547	.641	.375	.125	1.203	1/2	15/16	AS-113
4-DMC-2-ORT	400-1-2-OR	4M3SC2	1/4	1/8	1.375	.609	.703	.280	.187	1.094	9/16	3/4	AS-111
4-DMC-4-ORT	400-1-4-OR	4M3SC4	1/4	1/4	1.516	.609	.703	.375	.187	1.219	9/16	15/16	AS-113
6-DMC-6-ORT	600-1-6-OR	6M3SC6	3/8	3/8	1.625	.656	.766	.406	.281	1.344	11/16	1-1/8	AS-116
6-DMC-8-ORT	600-1-8-OR	6M3SC8	3/8	1/2	1.859	.656	.766	.531	.281	1.562	11/16	1-3/8	AS-212
8-DMC-4-ORT	810-1-4-OR	8M3SC4	1/2	1/4	1.687	.906	.875	.375	.281	1.281	7/8	15/16	AS-113
8-DMC-8-ORT	810-1-8-OR	8M3SC8	1/2	1/2	1.969	.906	.859	.531	.406	1.562	7/8	1-3/8	AS-212
10-DMC-12-ORT	1010-1-12-OR	10M3SC12	5/8	3/4	2.062	.969	.875	.562	.500	1.656	1	1-1/2	AS-215
12-DMC-12-ORT	1210-1-12-OR	12M3SC12	3/4	3/4	2.062	.969	.875	.562	.625	1.656	1-1/8	1-1/2	AS-215

\*NOTE: All dimensions subject to change, to be used for reference only.

\*\*NOTE: Stainless steel and carbon steel O-seal fittings up to 1 in. are rated to 3000 psi.


<sup>1</sup> The E dimension is the minimum opening. These fittings may have a larger opening at the pipe/straight thread end.

## Port Connector Union




PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	A	B	E THRU HOLE
1-DPCU-1	101-PC 1PC1	1/16	.547	.422	.031
2-DPCU-2	201-PC 2PC2	1/8	.875	.625	.094
4-DPCU-4	401-PC 4PC4	1/4	.969	.734	.187
5-DPCU-5	501-PC 5PC5	5/16	1.016	.797	.250
6-DPCU-6	601-PC 6PC6	3/8	1.031	.797	.297
8-DPCU-8	811-PC 8PC8	1/2	1.406	1.016	.391
12-DPCU-12	1211-PC 12PC12	3/4	1.469	1.094	.594
16-DPCU-16	1611-PC 16PC16	1	1.906	1.359	.812

\*NOTE: All dimensions subject to change, to be used for reference only.





## Reducer Adapter Tube to Tube



PART NUMBER	INTERCHANGES WITH	T1 TUBE O.D.	T2 TUBE O.D.	A	B	C	E THRU HOLE	L	NH NUT HEX	BH BODY HEX	
1-DRATT-2	100-R-2	2TUR1	1/16	1/8	1.156	.344	.437	.052	1.000	5/16	5/16
1-DRATT-4	100-R-4	4TUR1	1/16	1/4	1.234	.344	.437	.052	1.094	5/16	5/16
2-DRATT-1	200-R-1	1TUR2	1/8	1/16	1.141	.500	.609	.031	.875	7/16	7/16
2-DRATT-2	200-R-2	2TUR2	1/8	1/8	1.328	.500	.609	.078	1.062	7/16	7/16
2-DRATT-3	200-R-3	3TUR2	1/8	3/16	1.359	.500	.609	.094	1.094	7/16	7/16
2-DRATT-4	200-R-4	4TUR2	1/8	1/4	1.422	.500	.609	.094	1.156	7/16	7/16
2-DRATT-6	200-R-6	6TUR2	1/8	3/8	1.484	.500	.609	.094	1.219	7/16	7/16
2-DRATT-8	200-R-8	8TUR2	1/8	1/2	1.734	.500	.609	.094	1.484	7/16	9/16
3-DRATT-2	300-R-2	2TUR3	3/16	1/8	1.375	.547	.625	.078	1.109	1/2	7/16
3-DRATT-4	300-R-4	4TUR3	3/16	1/4	1.469	.547	.625	.125	1.203	1/2	7/16
4-DRATT-2	400-R-2	2TUR4	1/4	1/8	1.453	.609	.703	.078	1.156	9/16	1/2
4-DRATT-4	400-R-4	4TUR4	1/4	1/4	1.547	.609	.703	.187	1.250	9/16	1/2
4-DRATT-5	400-R-5	5TUR4	1/4	5/16	1.578	.609	.703	.187	1.281	9/16	1/2
4-DRATT-6	400-R-6	6TUR4	1/4	3/8	1.609	.609	.703	.187	1.312	9/16	1/2
4-DRATT-8	400-R-8	8TUR4	1/4	1/2	1.828	.609	.703	.187	1.531	9/16	9/16
4-DRATT-10	400-R-10	10TUR4	1/4	5/8	1.891	.609	.703	.187	1.609	9/16	11/16
5-DRATT-6	500-R-6	6TUR5	5/16	3/8	1.656	.641	.734	.250	1.359	5/8	9/16
5-DRATT-8	500-R-8	8TUR5	5/16	1/2	1.875	.641	.734	.250	1.578	5/8	9/16
6-DRATT-6	600-R-6	6TUR6	3/8	3/8	1.703	.656	.766	.281	1.406	11/16	5/8
6-DRATT-8	600-R-8	8TUR6	3/8	1/2	1.922	.656	.766	.281	1.625	11/16	5/8
6-DRATT-10	600-R-10	10TUR6	3/8	5/8	1.984	.656	.766	.281	1.687	11/16	11/16
6-DRATT-12	600-R-12	12TUR6	3/8	3/4	1.984	.656	.766	.281	1.687	11/16	13/16
8-DRATT-4	810-R-4	4TUR8	1/2	1/4	1.766	.906	.859	.187	1.375	7/8	13/16
8-DRATT-6	810-R-6	6TUR8	1/2	3/8	1.844	.906	.859	.281	1.437	7/8	13/16
8-DRATT-8	810-R-8	8TUR8	1/2	1/2	2.062	.906	.859	.406	1.656	7/8	13/16
8-DRATT-10	810-R-10	10TUR8	1/2	5/8	2.125	.906	.859	.406	1.719	7/8	13/16
8-DRATT-12	810-R-12	12TUR8	1/2	3/4	2.125	.906	.859	.406	1.719	7/8	13/16
8-DRATT-16	810-R-16	16TUR8	1/2	1	2.375	.906	.859	.406	1.969	7/8	1-1/16
10-DRATT-12	1010-R-12	12TUR10	5/8	3/4	2.156	.969	.859	.500	1.750	1	15/16
10-DRATT-14	1010-R-14	14TUR10	5/8	7/8	2.219	.969	.859	.500	1.812	1	15/16
10-DRATT-16	1010-R-16	16TUR10	5/8	1	2.406	.969	.859	.500	2.000	1	1-1/16
12-DRATT-8	1210-R-8	8TUR12	3/4	1/2	2.156	.969	.859	.391	1.750	1-1/8	1-1/16
12-DRATT-16	1210-R-16	16TUR12	3/4	1	2.469	.969	.859	.625	2.062	1-1/8	1-1/16


\*NOTE: All dimensions subject to change, to be used for reference only.

## Reducing Port Connector



PART NUMBER	INTERCHANGES WITH	T1 TUBE O.D.	T2 TUBE O.D.	A	B	E THRU HOLE	
2-DRPC-1	201-PC-1	1PC2	1/8	1/16	.687	.344	.031
4-DRPC-1	401-PC-1	1PC4	1/4	1/16	.719	.344	.031
4-DRPC-2	402-PC-2	2PC4	1/4	1/8	.891	.531	.094
6-DRPC-2	601-PC-2	2PC6	3/8	1/8	.906	.531	.094
6-DRPC-4	601-PC-4	4PC6	3/8	1/4	.984	.625	.187
8-DRPC-4	811-PC-4	4PC8	1/2	1/4	1.156	.625	.187
8-DRPC-6	811-PC-6	6PC8	1/2	3/8	1.203	.687	.281
12-DRPC-8	1211-PC-8	8PC12	3/4	1/2	1.437	.906	.391

\*NOTE: All dimensions subject to change, to be used for reference only.




## Reducing Union

PART NUMBER	INTERCHANGES WITH	T1 TUBE O.D.	T2 TUBE O.D.	A	B1	B2	C1	C2	D	E THRU HOLE	L	NH1 NUT HEX	NH2 NUT HEX	BH BODY HEX	
2-DRU-1	200-6-1	2RU1	1/8	1/16	1.219	.500	.344	.609	.437	.343	.052	.812	7/16	5/16	7/16
3-DRU-1	300-6-1	3RU1	3/16	1/16	1.266	.547	.344	.625	.437	.375	.052	.859	1/2	5/16	7/16
3-DRU-2	300-6-2	3RU2	3/16	1/8	1.437	.547	.500	.625	.609	.375	.094	.922	1/2	7/16	7/16
4-DRU-2	400-6-2	4RU2	1/4	1/8	1.516	.609	.500	.703	.609	.406	.094	.969	9/16	7/16	1/2
4-DRU-3	400-6-3	4RU3	1/4	3/16	1.547	.609	.547	.703	.625	.406	.125	1.000	9/16	1/2	1/2
5-DRU-2	500-6-2	5RU2	5/16	1/8	1.578	.641	.500	.734	.609	.437	.094	1.016	5/8	7/16	9/16
5-DRU-4	500-6-4	5RU4	5/16	1/4	1.656	.641	.609	.734	.703	.437	.187	1.078	5/8	9/16	9/16
6-DRU-1	600-6-1	6RU1	3/8	1/16	1.437	.656	.344	.765	.437	.468	.052	1.000	11/16	5/16	5/8
6-DRU-2	600-6-2	6RU2	3/8	1/8	1.609	.656	.500	.765	.609	.468	.094	1.062	11/16	7/16	5/8
6-DRU-4	600-6-4	6RU4	3/8	1/4	1.703	.656	.609	.765	.703	.468	.187	1.125	11/16	9/16	5/8
6-DRU-5	600-6-5	6RU5	3/8	5/16	1.734	.656	.641	.765	.734	.468	.250	1.156	11/16	5/8	5/8
8-DRU-2	810-6-2	8RU2	1/2	1/8	1.781	.906	.500	.859	.609	.468	.094	1.125	7/8	7/16	13/16
8-DRU-4	810-6-4	8RU4	1/2	1/4	1.859	.906	.609	.859	.703	.468	.187	1.156	7/8	9/16	13/16
8-DRU-6	810-6-6	8RU6	1/2	3/8	1.906	.906	.656	.859	.765	.468	.281	1.219	7/8	11/16	13/16
10-DRU-6	1010-6-6	10RU6	5/8	3/8	1.937	.969	.656	.859	.765	.468	.281	1.250	1	11/16	15/16
10-DRU-8	1010-6-8	10RU8	5/8	1/2	2.047	.969	.906	.859	.859	.468	.406	1.250	1	7/8	15/16
12-DRU-4	1210-6-4	12RU4	3/4	1/4	1.937	.969	.609	.859	.703	.468	.187	1.250	1-1/8	9/16	1-1/16
12-DRU-6	1210-6-6	12RU6	3/4	3/8	2.000	.969	.656	.859	.765	.468	.281	1.312	1-1/8	11/16	1-1/16
12-DRU-8	1210-6-8	12RU8	3/4	1/2	2.109	.969	.906	.859	.859	.468	.406	1.312	1-1/8	7/8	1-1/16
12-DRU-10	1210-6-10	12RU10	3/4	5/8	2.109	.969	.969	.859	.859	.468	.500	1.312	1-1/8	1	1-1/16
16-DRU-12	1610-6-12	16RU12	1	3/4	2.469	1.234	.969	1.047	.859	.562	.625	1.594	1-1/2	1-1/8	1-3/8

\*NOTE: All dimensions subject to change, to be used for reference only.


## Tube to Butt Weld Connector



PART NUMBER	INTERCHANGES WITH		T TUBE O.D.	BW	A	B	C	D	E <sup>1</sup> THRU HOLE	L	NH NUT HEX	BH BODY HEX
2-DTBW-2	200-1-2W	2-1/8 ZHLW2	1/8	.405	1.203	.500	.609	.375	.094	.937	7/16	7/16
3-DTBW-2	300-1-2W	3-1/8 ZHLW2	3/16	.405	1.234	.547	.625	.375	.125	.969	1/2	7/16
4-DTBW-2	400-1-2W	4-1/8 ZHLW2	1/4	.405	1.297	.609	.703	.375	.187	1.000	9/16	1/2
4-DTBW-4	400-1-4W	4-1/4 ZHLW2	1/4	.540	1.484	.609	.703	.562	.187	1.203	9/16	9/16
5-DTBW-4	500-1-4W	5-1/4 ZHLW2	5/16	.540	1.516	.641	.734	.562	.250	1.234	5/8	9/16
6-DTBW-4	600-1-4W	6-1/4 ZHLW2	3/8	.540	1.578	.656	.766	.562	.281	1.281	11/16	5/8
6-DTBW-6	600-1-6W	6-3/8 ZHLW2	3/8	.675	1.578	.656	.766	.562	.281	1.281	11/16	3/4
6-DTBW-8	600-1-8W	6-1/2 ZHLW2	3/8	.840	1.828	.656	.766	.750	.281	1.531	11/16	7/8
8-DTBW-6	810-1-6W	8-3/8 ZHLW2	1/2	.675	1.719	.906	.859	.562	.406	1.312	7/8	13/16
8-DTBW-8	810-1-8W	8-1/2 ZHLW2	1/2	.840	1.937	.906	.859	.750	.406	1.531	7/8	7/8
8-DTBW-12	810-1-12W	8-3/4 ZHLW2	1/2	1.050	1.984	.906	.859	.750	.406	1.594	7/8	1-1/16
10-DTBW-8	1010-1-8W	10-1/2 ZHLW2	5/8	.840	1.937	.969	.859	.750	.500	1.531	1	15/16
12-DTBW-12	1210-1-12W	12-3/4 ZHLW2	3/4	1.050	1.984	.969	.859	.750	.625	1.594	1-1/8	1-1/16
16-DTBW-16	1610-1-16W	16-1 ZHLW2	1	1.315	2.453	1.234	1.047	.937	.875	1.969	1-1/2	1-3/8

\*NOTE: All dimensions subject to change, to be used for reference only.

<sup>1</sup> The E dimension is the minimum opening. These fittings may have a larger opening at the pipe/straight thread end.




## Tube to Socket Weld Connector



PART NUMBER	INTERCHANGES WITH	T1 TUBE O.D.	T2 TUBE O.D.	A	B	C	D	E THRU HOLE	F	G	L	NH NUT HEX	BH BODY HEX
2-DTSW-2	200-6-2W 2-2 ZHLW	1/8	1/8	1.141	.500	.609	.344	.094	.312	.250	.875	7/16	7/16
3-DTSW-3	300-6-3W 3-3 ZHLW	3/16	3/16	1.172	.547	.641	.375	.125	.422	.203	.906	1/2	7/16
4-DTSW-4	400-6-4W 4-4 ZHLW	1/4	1/4	1.328	.609	.703	.406	.187	.437	.312	1.031	9/16	1/2
6-DTSW-6	600-6-6W 6-6 ZHLW	3/8	3/8	1.484	.656	.766	.469	.281	.609	.375	1.187	11/16	5/8
8-DTSW-8	810-6-8W 8-8 ZHLW	1/2	1/2	1.625	.906	.859	.469	.406	.750	.500	1.219	7/8	13/16
10-DTSW-10	1010-6-10W 10-10 ZHLW	5/8	5/8	1.656	.969	.859	.469	.500	.922	.500	1.250	1	15/16
12-DTSW-12	1210-6-12W 12-12 ZHLW	3/4	3/4	1.719	.969	.859	.469	.625	1.047	.562	1.312	1-1/8	1-1/16
16-DTSW-16	1610-6-16W 16-16 ZHLW	1	1	2.078	1.234	1.047	.562	.875	1.312	.750	1.594	1-1/2	1-3/8


\*NOTE: All dimensions subject to change, to be used for reference only.

## Union



PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	A	B	C	D	E THRU HOLE	L	NH NUT HEX	BH BODY HEX	
1-DU	100-6	1SC1	1/16	.984	.344	.437	.281	.052	.687	5/16	5/16
2-DU	200-6	2SC2	1/8	1.406	.500	.609	.343	.094	.875	7/16	7/16
3-DU	300-6	3SC3	3/16	1.469	.547	.625	.375	.125	.953	1/2	7/16
4-DU	400-6	4SC4	1/4	1.609	.609	.703	.406	.187	1.031	9/16	1/2
5-DU	500-6	5SC5	5/16	1.687	.641	.734	.437	.250	1.109	5/8	9/16
6-DU	600-6	6SC6	3/8	1.766	.656	.766	.468	.281	1.187	11/16	5/8
8-DU	810-6	8SC8	1/2	2.016	.906	.859	.468	.406	1.219	7/8	13/16
10-DU	1010-6	10SC10	5/8	2.047	.969	.859	.468	.500	1.250	1	15/16
12-DU	1210-6	12SC12	3/4	2.109	.969	.859	.468	.625	1.312	1-1/8	1-1/16
14-DU	1410-6	14SC14	7/8	2.187	1.016	.859	.468	.718	1.375	1-1/4	1-3/16
16-DU	1610-6	16SC16	1	2.547	1.234	1.047	.562	.875	1.594	1-1/2	1-3/8

\*NOTE: All dimensions subject to change, to be used for reference only.



## Tube to AN Flare Union





PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	J THREAD	A	B	C	D	E <sup>1</sup> THRU HOLE	L	NH NUT HEX	BH BODY HEX	
2-DUANF-2	200-6-2AN	2XASC2	1/8	5/16-24	1.234	.500	.609	.448	.062	.984	7/16	7/16
2-DUANF-4	200-6-4AN	4XASC2	1/8	7/16-20	1.375	.500	.609	.550	.094	1.125	7/16	1/2
3-DUANF-3	300-6-3AN	3XASC3	3/16	3/8-24	1.328	.547	.641	.479	.125	1.062	1/2	7/16
4-DUANF-4	400-6-4AN	4XASC4	1/4	7/16-20	1.484	.609	.703	.550	.172	1.187	9/16	1/2
5-DUANF-5	500-6-5AN	5XASC5	5/16	1/2-20	1.516	.641	.734	.550	.234	1.219	5/8	9/16
6-DUANF-4	600-6-4AN	4XASC6	3/8	7/16-20	1.562	.656	.766	.550	.172	1.266	11/16	5/8
6-DUANF-6	600-6-6AN	6XASC6	3/8	9/16-18	1.562	.656	.766	.556	.297	1.266	11/16	5/8
8-DUANF-8	810-6-8AN	8XASC8	1/2	3/4-16	1.812	.906	.859	.657	.391	1.406	7/8	13/16
10-DUANF-10	1010-6-10AN	10XASC10	5/8	7/8-14	1.937	.969	.875	.758	.484	1.531	1	15/16
12-DUANF-12	1210-6-12AN	12XASC12	3/4	1-1/16-12	2.109	.969	.859	.864	.609	1.703	1-1/8	1-1/8
16-DUANF-16	1610-6-16AN	16XASC16	1	1-5/16-12	2.422	1.234	1.047	.911	.844	1.937	1-1/2	1-3/8

\*NOTE: All dimensions subject to change, to be used for reference only.



<sup>1</sup> The E dimension is the minimum opening. These fittings may have a larger opening at the pipe/straight thread end.

## Union Elbow



PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	A	B	C	E THRU HOLE	L	NH NUT HEX	W WRENCH FLAT	
1-DELU-1	100-9	1EE1	1/16	.750	.344	.437	.052	.609	5/16	7/16
2-DELU-2	200-9	2EE2	1/8	.875	.500	.609	.094	.625	7/16	3/8
3-DELU-3	300-9	3EE3	3/16	1.000	.547	.625	.125	.734	1/2	1/2
4-DELU-4	400-9	4EE4	1/4	1.062	.609	.703	.187	.766	9/16	1/2
5-DELU-5	500-9	5EE5	5/16	1.125	.640	.734	.250	.844	5/8	9/16
6-DELU-6	600-9	6EE6	3/8	1.203	.656	.766	.281	.906	11/16	5/8
8-DELU-8	810-9	8EE8	1/2	1.421	.906	.859	.406	1.016	7/8	13/16
10-DELU-10	1010-9	10EE10	5/8	1.500	.969	.859	.500	1.109	1	15/16
12-DELU-12	1210-9	12EE12	3/4	1.578	.969	.859	.625	1.171	1-1/8	1-1/16
14-DELU-14	1410-9	14EE14	7/8	1.766	1.016	.859	.718	1.406	1-1/4	1-3/8
16-DELU-16	1610-9	16EE16	1	1.937	1.234	1.047	.875	1.438	1-1/2	1-3/8

\*NOTE: All dimensions subject to change, to be used for reference only.





Female Elbow

PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	P PIPE END NPT	A1	A2	B	C	E THRU HOLE	L	NH NUT HEX	W WRENCH FLAT	
1-DFE-2	100-8-2	1FEL2N	1/16	1/8	.812	.750	.500	.609	.052	.687	5/16	1/2
2-DFE-2	200-8-2	2FEL2N	1/8	1/8	.969	.750	.500	.609	.094	.719	7/16	1/2
2-DFE-4	200-8-4	2FEL4N	1/8	1/4	1.078	.875	.500	.609	.094	.828	7/16	11/16
3-DFE-2	300-8-2	3FEL2N	3/16	1/8	1.000	.750	.547	.625	.125	.734	1/2	1/2
4-DFE-2	400-8-2	4FEL2N	1/4	1/8	1.062	.750	.609	.703	.187	.781	9/16	1/2
4-DFE-4	400-8-4	4FEL4N	1/4	1/4	1.172	.875	.609	.703	.187	.875	9/16	11/16
4-DFE-6	400-8-6	4FEL6N	1/4	3/8	1.250	.875	.609	.703	.187	.969	9/16	13/16
4-DFE-8	400-8-8	4FEL8N	1/4	1/2	1.359	1.125	.609	.703	.187	1.078	9/16	1
5-DFE-2	500-8-2	5FEL2N	5/16	1/8	1.125	.750	.640	.734	.250	.844	5/8	9/16
5-DFE-4	500-8-4	5FEL4N	5/16	1/4	1.203	.875	.640	.734	.250	.906	5/8	11/16
6-DFE-2	600-8-2	6FEL2N	3/8	1/8	1.203	.750	.656	.766	.281	.906	11/16	5/8
6-DFE-4	600-8-4	6FEL4N	3/8	1/4	1.234	.875	.656	.766	.281	.937	11/16	11/16
6-DFE-6	600-8-6	6FEL6N	3/8	3/8	1.312	.875	.656	.766	.281	1.016	11/16	13/16
6-DFE-8	600-8-8	6FEL8N	3/8	1/2	1.429	1.125	.656	.766	.281	1.125	11/16	1
8-DFE-4	810-8-4	8FEL4N	1/2	1/4	1.429	.875	.906	.859	.406	1.016	7/8	13/16
8-DFE-6	810-8-6	8FEL6N	1/2	3/8	1.429	.875	.906	.859	.406	1.016	7/8	13/16
8-DFE-8	810-8-8	8FEL8N	1/2	1/2	1.531	1.125	.906	.859	.406	1.125	7/8	1
10-DFE-6	1010-8-6	10FEL6N	5/8	3/8	1.500	.875	.969	.859	.500	1.109	1	15/16
10-DFE-8	1010-8-8	10FEL8N	5/8	1/2	1.578	1.125	.969	.859	.500	1.171	1	1-1/16
12-DFE-8	1210-8-8	12FEL8N	3/4	1/2	1.578	1.125	.969	.859	.625	1.171	1-1/8	1-1/16
12-DFE-12	1210-8-12	12FEL12N	3/4	3/4	1.766	1.250	.969	.859	.625	1.359	1-1/8	1-3/8
14-DFE-12	1410-8-12	14FEL12N	7/8	3/4	1.766	1.250	1.016	.859	.718	1.359	1-1/4	1-3/8
16-DFE-12	1610-8-12	16FEL12N	1	3/4	1.937	1.250	1.234	1.049	.875	1.453	1-1/2	1-3/8
16-DFE-16	1610-8-16	16FEL16N	1	1	1.984	1.500	1.234	1.049	.875	1.500	1-1/2	1-11/16

\*NOTE: All dimensions subject to change, to be used for reference only.



## Male Elbow



PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	P PIPE END NPT	A1	A2	B	C	D	E <sup>1</sup> THRU HOLE	L	NH NUT HEX	W WRENCH FLAT	
1-DME-1	100-2-1	1MSEL1N	1/16	1/16	.703	.656	.344	.437	.375	.052	.547	5/16	3/8
1-DME-2	100-2-2	1MSEL2N	1/16	1/8	.750	.703	.344	.437	.375	.052	.609	5/16	7/16
2-DME-1	200-2-1	2MSEL1N	1/8	1/16	.937	.703	.500	.609	.375	.094	.672	7/16	7/16
2-DME-2	200-2-2	2MSEL2N	1/8	1/8	.937	.703	.500	.609	.375	.094	.672	7/16	7/16
2-DME-4	200-2-4	2MSEL4N	1/8	1/4	.969	.922	.500	.609	.562	.094	.719	7/16	1/2
2-DME-6	200-2-6	2MSEL6N	1/8	3/8	1.203	1.125	.500	.609	.562	.094	.812	7/16	13/16
3-DME-2	300-2-2	3MSEL2N	3/16	1/8	1.000	.734	.547	.625	.375	.125	.734	1/2	1/2
3-DME-4	300-2-4	3MSEL4N	3/16	1/4	1.000	.922	.547	.625	.562	.125	.734	1/2	1/2
4-DME-1	400-2-1	4MSEL1N	1/4	1/16	1.203	.703	.609	.703	.375	.156	.719	9/16	1/2
4-DME-2	400-2-2	4MSEL2N	1/4	1/8	1.062	.734	.609	.703	.375	.187	.766	9/16	1/2
4-DME-4	400-2-4	4MSEL4N	1/4	1/4	1.062	.922	.609	.703	.562	.187	.766	9/16	1/2
4-DME-6	400-2-6	4MSEL6N	1/4	3/8	1.172	1.031	.609	.703	.562	.187	.875	9/16	11/16
4-DME-8	400-2-8	4MSEL8N	1/4	1/2	1.250	1.297	.609	.703	.750	.187	.969	9/16	13/16
4-DME-12	400-2-12	4MSEL12N	1/4	3/4	1.546	1.500	.609	.703	.750	.187	1.093	9/16	1-1/16
5-DME-2	500-2-2	5MSEL2N	5/16	1/8	1.125	.781	.641	.734	.375	.187	.844	5/8	9/16
5-DME-4	500-2-4	5MSEL4N	5/16	1/4	1.125	.969	.641	.734	.562	.250	.844	5/8	9/16
5-DME-6	500-2-6	5MSEL6N	5/16	3/8	1.203	1.031	.641	.734	.562	.250	.906	5/8	11/16
6-DME-2	600-2-2	6MSEL2N	3/8	1/8	1.203	.812	.656	.766	.375	.187	.906	11/16	5/8
6-DME-4	600-2-4	6MSEL4N	3/8	1/4	1.203	1.000	.656	.766	.562	.281	.906	11/16	5/8
6-DME-6	600-2-6	6MSEL6N	3/8	3/8	1.234	1.031	.656	.766	.562	.281	.937	11/16	11/16

\*NOTE: All dimensions subject to change, to be used for reference only.

<sup>1</sup> The E dimension is the minimum opening. These fittings may have a larger opening at the pipe/straight thread end.



## Male Elbow





PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	P PIPE END NPT	A1	A2	B	C	D	E <sup>1</sup> THRU HOLE	L	NH NUT HEX	W WRENCH FLAT	
6-DME-8	600-2-8	6MSEL8N	3/8	1/2	1.312	1.297	.656	.766	.750	.281	1.016	11/16	13/16
6-DME-12	600-2-12	6MSEL12N	3/8	3/4	1.469	1.453	.656	.766	.750	.281	1.172	11/16	1-1/16
8-DME-2	810-2-2	8MSEL2N	1/2	1/8	1.609	1.109	.906	.859	.375	.187	.969	7/8	13/16
8-DME-4	810-2-4	8MSEL4N	1/2	1/4	1.422	1.109	.906	.859	.562	.281	1.016	7/8	13/16
8-DME-6	810-2-6	8MSEL6N	1/2	3/8	1.422	1.109	.906	.859	.562	.375	1.016	7/8	13/16
8-DME-8	810-2-8	8MSEL8N	1/2	1/2	1.422	1.297	.906	.859	.750	.406	1.016	7/8	13/16
8-DME-12	810-2-12	8MSEL12N	1/2	3/4	1.578	1.453	.906	.859	.750	.406	1.172	7/8	1-1/16
10-DME-4	1010-2-4	10MSEL4N	5/8	1/4	1.498	1.125	.969	.859	.562	.281	1.093	1	1
10-DME-6	1010-2-6	10MSEL6N	5/8	3/8	1.500	1.187	.969	.859	.562	.375	1.109	1	15/16
10-DME-8	1010-2-8	10MSEL8N	5/8	1/2	1.500	1.375	.969	.859	.750	.469	1.109	1	15/16
10-DME-12	1010-2-12	10MSEL12N	5/8	3/4	1.578	1.453	.969	.859	.750	.500	1.172	1	1-1/16
10-DME-16	1010-2-16	10MSEL16N	5/8	1	1.780	1.844	.969	.859	.937	.500	1.375	1	1-1/2
12-DME-4	1210-2-4	12MSEL4N	3/4	1/4	1.576	1.250	.969	.859	.562	.281	1.375	1-1/8	1-1/16
12-DME-6	1210-2-6	12MSEL6N	3/4	3/8	1.576	1.250	.969	.859	.562	.406	1.375	1-1/8	1-1/16
12-DME-8	1210-2-8	12MSEL8N	3/4	1/2	1.561	1.453	.969	.859	.750	.469	1.172	1-1/8	1-1/16
12-DME-12	1210-2-12	12MSEL12N	3/4	3/4	1.578	1.453	.969	.859	.750	.625	1.172	1-1/8	1-1/16
14-DME-12	1410-2-12	14MSEL12N	7/8	3/4	1.766	1.641	1.016	.859	.750	.625	1.359	1-1/4	1-3/8
16-DME-4	1610-2-4	16MSEL4N	1	1/4	1.935	1.375	1.234	1.047	.562	.281	1.531	1-1/2	1-1/2
16-DME-8	1610-2-8	16MSEL8N	1	1/2	1.935	1.562	1.234	1.047	.750	.500	1.531	1-1/2	1-1/2
16-DME-12	1610-2-12	16MSEL12N	1	3/4	1.937	1.641	1.234	1.047	.937	.625	1.453	1-1/2	1-3/8
16-DME-16	1610-2-16	16MSEL16N	1	1	1.937	1.828	1.234	1.047	.937	.875	1.453	1-1/2	1-3/8

\*NOTE: All dimensions subject to change, to be used for reference only.

<sup>1</sup> The E dimension is the minimum opening. These fittings may have a larger opening at the pipe/straight thread end.


## Tube to Butt Weld Elbow



PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	BW	A1	A2	B	C	D	E <sup>1</sup> THRU HOLE	L	NH NUT HEX	W WRENCH FLAT
2-DTBWE-2	200-2-2W 2-1/8 ZELW2	1/8	.405	.922	.719	.516	.609	.344	.094	.656	7/16	1/2
3-DTBWE-2	300-2-2W 3-1/8 ZELW2	3/16	.405	1.016	.734	.547	.641	.375	.125	.734	1/2	1/2
4-DTBWE-2	400-2-2W 4-1/8 ZELW2	1/4	.405	1.062	.734	.609	.703	.375	.187	.766	9/16	1/2
4-DTBWE-4	400-2-4W 4-1/4 ZELW2	1/4	.540	1.062	.937	.609	.703	.562	.187	.766	9/16	1/2
6-DTBWE-4	600-2-4W 6-1/4 ZELW2	3/8	.540	1.203	1.000	.656	.766	.562	.281	.906	11/16	5/8
8-DTBWE-6	800-2-6W 8-3/8 ZELW2	1/2	.675	1.375	1.125	.906	.859	.562	.406	.969	7/8	13/16
8-DTBWE-8	810-2-8W 8-1/2 ZELW2	1/2	.840	1.422	1.297	.906	.859	.750	.406	1.016	7/8	13/16
10-DTBWE-8	1010-2-8W 10-1/2 ZELW2	5/8	.840	1.437	1.312	.969	.859	.750	.500	1.031	1	7/8
12-DTBWE-12	1210-2-12W 12-3/4 ZELW2	3/4	1.050	1.578	1.453	.969	.859	.750	.625	1.172	1-1/8	1-1/16
16-DTBWE-12	1610-2-12W 16-3/4 ZELW2	1	1.050	1.937	1.625	1.234	1.047	.750	.875	1.453	1-1/2	1-5/16
16-DTBWE-16	1610-2-16W 16-1 ZELW2	1	1.315	1.937	1.844	1.234	1.047	.937	.875	1.453	1-1/2	1-5/16

\*NOTE: All dimensions subject to change, to be used for reference only.



<sup>1</sup> The E dimension is the minimum opening. These fittings may have a larger opening at the pipe/straight thread end.



PART NUMBER	INTERCHANGES WITH		T TUBE O.D.	A1	A2	B	C	D	E THRU HOLE	F	L	NH NUT HEX	W WRENCH FLAT
2-DTSWE-2	200-9-2W	2-2 ZELWZ	1/8	.922	.625	.516	.609	.156	.094	.375	.656	7/16	5/16
3-DTSWE-3	300-9-3W	3-3 ZELWZ	3/16	.984	.687	.547	.641	.203	.125	.437	.719	1/2	7/16
4-DTSWE-4	400-9-4W	4-4 ZELWZ	1/4	1.062	.766	.609	.703	.312	.187	.500	.766	9/16	1/2
6-DTSWE-6	600-9-6W	6-6 ZELWZ	3/8	1.203	.906	.656	.766	.375	.281	.625	.875	11/16	5/8
8-DTSWE-8	810-9-8W	8-8 ZELWZ	1/2	1.422	1.016	.906	.859	.500	.406	.812	1.016	7/8	13/16
10-DTSWE-10	1010-9-10W	10-10 ZELWZ	5/8	1.562	1.156	.969	.875	.500	.500	.937	1.156	1	1-1/16
12-DTSWE-12	1210-9-12W	12-12 ZELWZ	3/4	1.562	1.312	.969	.875	.500	.625	1.094	1.156	1-1/8	1-1/16
16-DTSWE-16	1610-9-16W	16-16 ZELWZ	1	1.937	1.469	1.234	1.047	.562	.875	1.375	1.453	1-1/2	1-5/16



\*NOTE: All dimensions subject to change, to be used for reference only.

## Female Run Tee



PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	P PIPE END NPT	A	A1	A2	B	C	E THRU HOLE	L	NH NUT HEX	W WRENCH FLAT
2-DTFT-2	200-3TFT 2FRT2N	1/8	1/8	1.719	.969	.750	.500	.609	.094	.719	7/16	1/2
3-DTFT-2	300-3-2TFT 3FRT2N	3/16	1/8	1.766	1.016	.750	.547	.641	.125	.750	1/2	9/16
4-DTFT-2	400-3TFT 4FRT2N	1/4	1/8	1.812	1.078	.750	.609	.703	.187	.781	9/16	9/16
4-DTFT-4	400-3-4TFT 4FRT4N	1/4	1/4	2.047	1.172	.875	.609	.703	.187	.875	9/16	11/16
5-DTFT-2	500-3-2TFT 5FRT2N	5/16	1/8	1.922	1.172	.750	.641	.734	.250	.875	5/8	5/8
6-DTFT-4	600-3TFT 6FRT4N	3/8	1/4	2.109	1.234	.875	.656	.766	.281	.937	11/16	11/16
8-DTFT-4	810-3-4TFT 8FRT4N	1/2	1/4	2.562	1.437	1.125	.906	.875	.406	1.125	7/8	13/16
8-DTFT-6	810-3TFT 8FRT6N	1/2	3/8	2.297	1.422	.875	.906	.859	.406	1.016	7/8	13/16
8-DTFT-8	810-3-8TFT 8FRT8N	1/2	1/2	2.687	1.578	1.125	.906	.859	.406	1.172	7/8	1-1/16
10-DTFT-8	1010-3-8TFT 10FRT8N	5/8	1/2	2.656	1.531	1.125	.969	.875	.500	1.125	1	1-1/16
12-DTFT-12	1210-3-TFT 12FRT12N	3/4	3/4	3.016	1.766	1.250	.969	.859	.625	1.359	1-1/8	1-3/8
14-DTFT-12	1410-3-12TFT 14FRT12N	7/8	3/4	3.016	1.766	1.250	1.031	.875	.750	1.359	1-1/4	1-5/16
16-DTFT-12	1610-3-12TFT 16FRT12N	1	3/4	3.187	1.937	1.250	1.234	1.047	.875	1.453	1-1/2	1-5/16
16-DTFT-16	1610-3TFT 16FRT16N	1	1	3.516	2.016	1.500	1.234	1.047	.875	1.531	1-1/2	1-5/8

\*NOTE: All dimensions subject to change, to be used for reference only.





PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	P PIPE END NPT	A	A1	A2	B	C	D	E <sup>1</sup> THRU HOLE	L	NH NUT HEX	W WRENCH FLAT
2-DTMT-2	200-3TMT 2MRT2N	1/8	1/8	1.625	.937	.703	.500	.609	.375	.094	.672	7/16	7/16
3-DTMT-2	300-3TMT 3MRT2N	3/16	1/8	1.656	.969	.703	.547	.625	.375	.125	.703	1/2	7/16
4-DTMT-2	400-3TMT 4MRT2N	1/4	1/8	1.797	1.062	.734	.609	.703	.375	.187	.766	9/16	1/2
4-DTMT-4	400-3-4TMT 4MRT4N	1/4	1/4	1.984	1.062	.922	.609	.703	.562	.187	.766	9/16	5/8
5-DTMT-2	500-3TMT 5MRT2N	5/16	1/8	1.984	1.172	.828	.641	.725	.375	.187	.875	5/8	5/8
6-DTMT-4	600-3TMT 6MRT4N	3/8	1/4	2.203	1.203	1.000	.656	.766	.562	.281	.906	11/16	5/8
6-DTMT-6	600-3-6TMT 6MRT6N	3/8	3/8	2.422	1.312	1.109	.656	.766	.562	.281	1.016	11/16	13/16
8-DTMT-6	810-3TMT 8MRT6N	1/2	3/8	2.531	1.422	1.109	.906	.859	.562	.406	1.016	7/8	13/16
8-DTMT-8	810-3-8TMT 8MRT8N	1/2	1/2	2.719	1.422	1.297	.906	.859	.750	.406	1.016	7/8	13/16
10-DTMT-8	1010-3TMT 10MRT8N	5/8	1/2	2.875	1.500	1.375	.969	.859	.750	.469	1.109	1	15/16
12-DTMT-12	1210-3TMT 12MRT12N	3/4	3/4	3.016	1.578	1.453	.969	.859	.750	.625	1.172	1-1/8	1-1/16
14-DTMT-12	1410-3-12TMT 14MRT12N	7/8	3/4	3.266	1.766	1.500	1.031	.875	.750	.750	1.359	1-1/4	1-5/16
16-DTMT-12	1610-3-12TMT 16MRT12N	1	3/4	3.609	1.937	1.656	1.234	1.047	.750	.875	1.453	1-1/2	1-5/16
16-DTMT-16	1610-3-16TMT 16MRT16N	1	1	3.781	1.937	1.844	1.234	1.047	.937	.875	1.453	1-1/2	1-5/16

\*NOTE: All dimensions subject to change, to be used for reference only.


<sup>1</sup> The E dimension is the minimum opening. These fittings may have a larger opening at the pipe/straight thread end.

## Female Branch Tee



PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	P PIPE END NPT	A	A1	A2	B	C	E THRU HOLE	L	NH NUT HEX	W WRENCH FLAT	
2-DTTF-2	200-3TTF	2FBT2N	1/8	1/8	1.937	.969	.750	.500	.609	.094	.719	7/16	1/2
3-DTTF-2	300-3-2TTF	3FBT2N	3/16	1/8	2.016	1.016	.750	.547	.641	.125	.750	1/2	1/2
4-DTTF-2	400-3TTF	4FBT2N	1/4	1/8	2.125	1.062	.750	.609	.703	.187	.766	9/16	1/2
4-DTTF-4	400-3-4TTF	4FBT4N	1/4	1/4	2.344	1.172	.875	.609	.703	.187	.875	9/16	11/16
5-DTTF-2	500-3-2TTF	5FBT2N	5/16	1/8	2.344	1.172	.750	.641	.734	.250	.875	5/8	5/8
6-DTTF-4	600-3TTF	6FBT4N	3/8	1/4	2.469	1.234	.875	.656	.766	.281	.937	11/16	11/16
8-DTTF-4	810-3-4TTF	8FBT4N	1/2	1/4	2.844	1.422	.875	.906	.859	.406	1.016	7/8	13/16
8-DTTF-6	810-3TTF	8FBT6N	1/2	3/8	2.844	1.422	.875	.906	.859	.406	1.016	7/8	13/16
8-DTTF-8	810-3-8TTF	8FBT8N	1/2	1/2	3.062	1.531	1.125	.906	.859	.406	1.125	7/8	1
10-DTTF-8	1010-3TTF	10FBT8N	5/8	1/2	3.062	1.531	1.125	.969	.859	.500	1.125	1	1
12-DTTF-12	1210-3TTF	12FBT12N	3/4	3/4	3.516	1.766	1.250	.969	.859	.625	1.359	1-1/8	1-3/8
14-DTTF-12	1410-3-12TTF	14FBT12N	7/8	3/4	3.016	1.766	1.250	1.031	.875	.750	1.359	1-1/4	1-5/16
16-DTTF-12	1610-3-12TTF	16FBT12N	1	3/4	3.859	1.937	1.250	1.234	1.047	.875	1.453	1-1/2	1-3/8
16-DTTF-16	1610-3TTF	16FBT16N	1	1	3.969	1.984	1.500	1.234	1.047	.875	1.500	1-1/2	1-11/16

\*NOTE: All dimensions subject to change, to be used for reference only.





PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	P PIPE END NPT	A	A1	A2	B	C	D	E <sup>1</sup> THRU HOLE	L	NH NUT HEX	W WRENCH FLAT	
2-DTTM-2	200-3TTM	2MBT2N	1/8	1/8	1.859	.937	.703	.500	.609	.375	.094	.672	7/16	7/16
2-DTTM-4	200-3-4TTM	2MBT4N	1/8	1/4	1.937	.969	.922	.500	.609	.562	.094	.719	7/16	1/2
3-DTTM-2	300-3TTM	3MBT2N	3/16	1/8	1.922	.969	.703	.547	.625	.375	.125	.703	1/2	7/16
4-DTTM-2	400-3TTM	4MBT2N	1/4	1/8	2.125	1.062	.734	.609	.703	.375	.187	.765	9/16	1/2
4-DTTM-4	400-3-4TTM	4MBT4N	1/4	1/4	2.125	1.062	.922	.609	.703	.562	.187	.765	9/16	1/2
5-DTTM-2	500-3TTM	5MBT2N	5/16	1/8	2.344	1.172	.828	.641	.725	.375	.187	.875	5/8	5/8
6-DTTM-4	600-3TTM	6MBT4N	3/8	1/4	2.406	1.203	1.000	.656	.765	.562	.281	.906	11/16	5/8
6-DTTM-6	600-3-6TTM	6MBT6N	3/8	3/8	2.625	1.312	1.109	.656	.765	.562	.281	1.016	11/16	13/16
8-DTTM-6	810-3TTM	8MBT6N	1/2	3/8	2.844	1.422	1.109	.906	.859	.562	.375	1.016	7/8	13/16
8-DTTM-8	810-3-8TTM	8MBT8N	1/2	1/2	2.844	1.422	1.297	.906	.859	.750	.406	1.016	7/8	13/16
10-DTTM-8	1010-3TTM	10MBT8N	5/8	1/2	3.062	1.531	1.406	.969	.859	.750	.469	1.125	1	1
12-DTTM-12	1210-3TTM	12MBT12N	3/4	3/4	3.141	1.172	1.453	.969	.859	.750	.625	1.172	1-1/8	1-1/16
14-DTTM-12	1410-3-12TTM	14MBT12N	7/8	3/4	3.516	1.766	1.500	1.031	.875	.750	.750	1.359	1-1/4	1-3/8
16-DTTM-12	1610-3-12TTM	16MBT12N	1	3/4	3.875	1.937	1.656	1.234	1.047	.750	.875	1.453	1-1/2	1-1/2
16-DTTM-16	1610-3-16TTM	16MBT16N	1	1	3.875	1.937	1.656	1.234	1.047	.937	.875	1.453	1-1/2	1-5/16

\*NOTE: All dimensions subject to change, to be used for reference only.



<sup>1</sup> The E dimension is the minimum opening. These fittings may have a larger opening at the pipe/straight thread end.

## Union Tee



PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	A	A1	B	C	E THRU HOLE	L	NH NUT HEX	W WRENCH FLAT
1-DTTT-1	100-3 1ET1	1/16	1.406	.703	.344	.437	.052	.547	5/16	3/8
2-DTTT-2	200-3 2ET2	1/8	1.766	.875	.500	.609	.094	.625	7/16	3/8
3-DTTT-3	300-3 3ET3	3/16	1.922	.969	.547	.625	.125	.703	1/2	7/16
4-DTTT-4	400-3 4ET4	1/4	2.125	1.062	.609	.703	.187	.766	9/16	1/2
5-DTTT-5	500-3 5ET5	5/16	2.344	1.172	.641	.734	.250	.875	5/8	5/8
6-DTTT-6	600-3 6ET6	3/8	2.406	1.203	.656	.766	.281	.906	11/16	5/8
8-DTTT-8	810-3 8ET8	1/2	2.844	1.422	.906	.859	.406	1.016	7/8	13/16
10-DTTT-10	1010-3 10ET10	5/8	3.062	1.531	.969	.859	.500	1.125	1	1
12-DTTT-12	1210-3 12ET12	3/4	3.141	1.578	.969	.859	.625	1.172	1-1/8	1-1/16
14-DTTT-14	1410-3 14ET14	7/8	3.516	1.766	1.016	.859	.718	1.359	1-1/4	1-3/8
16-DTTT-16	1610-3 16ET16	1	3.859	1.937	1.234	1.047	.875	1.453	1-1/2	1-3/8

\*NOTE: All dimensions subject to change, to be used for reference only.





PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	A	A1	B	C	E THRU HOLE	L	NH NUT HEX	W WRENCH FLAT
2-DCR	200-4      2ECR2	1/8	1.766	.875	.500	.609	.094	.625	7/16	3/8
4-DCR	400-4      4ECR4	1/4	2.125	1.062	.609	.703	.187	.766	9/16	1/2
5-DCR	500-4      5ECR5	5/16	2.344	1.172	.641	.734	.250	.875	5/8	5/8
6-DCR	600-4      6ECR6	3/8	2.406	1.203	.656	.766	.281	.906	11/16	5/8
8-DCR	810-4      8ECR8	1/2	2.844	1.422	.906	.859	.406	1.016	7/8	13/16
12-DCR	1210-4     12ECR12	3/4	3.016	1.516	.969	.859	.625	1.109	1-1/8	1-1/16
16-DCR	1610-4     16ECR16	1	3.687	1.844	1.234	1.047	.875	1.359	1-1/2	1-3/8

\*NOTE: All dimensions subject to change, to be used for reference only.

\*All tube ends are typical.



# Barbed Insert



PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	W REF.	A	E THRU HOLE	F TUBE I.D.	L
3-DBI-030	305-2	3/16	.031	.566	.062	1/8	.518
4-DBI-022	405-2	1/4	.022	.566	.141	13/64	.518
4-DBI-031	405-3	1/4	.031	.566	.125	3/16	.518
4-DBI-040	405-170	1/4	.040	.566	.109	11/64	.518
4-DBI-062		1/4	.062	.566	.062	1/8	.518
5-DBI-031	505-4	5/16	.031	.566	.187	1/4	.518
5-DBI-062	505-3	5/16	.062	.566	.125	3/16	.518
5-DBI-094	505-2	5/16	.094	.566	.062	1/8	.518
5-DBI-103		5/16	.103	.566	.045	7/64	.518
6-DBI-049		3/8	.049	.566	.218	9/32	.518
6-DBI-062	605-4	3/8	.062	.566	.187	1/4	.518
6-DBI-094	605-3	3/8	.094	.566	.125	3/16	.518
6-DBI-159		3/8	.159	.566	.032	1/16	.518
8-DBI-035		1/2	.035	.750	.375	7/16	.702
8-DBI-049		1/2	.049	.750	.344	13/32	.702
8-DBI-062	815-6	1/2	.062	.750	.312	3/8	.702
8-DBI-125	815-4	1/2	.125	.750	.187	1/4	.702
10-DBI-049		5/8	.049	.750	.469	17/32	.702
10-DBI-062	1015-8	5/8	.062	.750	.437	1/2	.702
10-DBI-125	1015-6	5/8	.125	.750	.312	3/8	.702
10-DBI-187		5/8	.187	.750	.187	1/4	.702
12-DBI-049		3/4	.049	.750	.562	21/32	.702
12-DBI-062	1215-10	3/4	.062	.750	.562	5/8	.702
12-DBI-125	1215-8	3/4	.125	.750	.437	1/2	.702
14-DBI-049		7/8	.049	1.031	.687	25/32	.938
14-DBI-062		7/8	.062	1.031	.687	3/4	.938
14-DBI-125		7/8	.125	1.031	.562	5/8	.938
16-DBI-062	1615-14	1	.062	1.031	.812	7/8	.938
16-DBI-125	1615-12	1	.125	1.031	.687	3/4	.938

\*NOTE: All dimensions subject to change, to be used for reference only.


## Plane Insert



PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	W REF.	A	E THRU HOLE	F TUBE I.D.	L
3-DPI-030	3 TIZ (.125)	3/16	.031	.566	.062	1/8	.518
4-DPI-022		1/4	.022	.566	.140	13/64	.518
4-DPI-031	4 TIZ (.188)	1/4	.031	.566	.125	3/16	.518
4-DPI-040	4 TIZ (.170)	1/4	.040	.566	.109	11/64	.518
5-DPI-062	5 TIZ (.188)	5/16	.062	.566	.125	3/16	.518
5-DPI-094	5 TIZ (.125)	5/16	.094	.566	.062	1/8	.518
6-DPI-049		3/8	.049	.566	.218	9/32	.518
6-DPI-062	6 TIZ (.250)	3/8	.062	.566	.187	1/4	.518
6-DPI-094	6 TIZ (.188)	3/8	.094	.566	.125	3/16	.518
8-DPI-035		1/2	.035	.750	.375	7/16	.702
8-DPI-049		1/2	.049	.750	.344	13/32	.702
8-DPI-062	8 TIZ (.375)	1/2	.062	.750	.312	3/8	.702
8-DPI-125	8 TIZ (.250)	1/2	.125	.750	.187	1/4	.702
10-DPI-049		5/8	.049	.750	.469	17/32	.702
10-DPI-062	10 TIZ (.500)	5/8	.062	.750	.437	1/2	.702
10-DPI-125	10 TIZ (.375)	5/8	.125	.750	.312	3/8	.702
12-DPI-049		3/4	.049	.750	.562	21/32	.702
12-DPI-062	12 TIZ (.625)	3/4	.062	.750	.562	5/8	.702
12-DPI-125	12 TIZ (.500)	3/4	.125	.750	.437	1/2	.702
14-DPI-049		7/8	.049	1.000	.687	25/32	.952
14-DPI-062		7/8	.062	1.000	.687	3/4	.952
14-DPI-125		7/8	.125	1.000	.562	5/8	.952
16-DPI-050		1	.050	1.000	.843	57/64	.952
16-DPI-062	16 TIZ (.875)	1	.062	1.000	.812	7/8	.952
16-DPI-125	16 TIZ (.750)	1	.125	1.000	.687	3/4	.952

\*NOTE: All dimensions subject to change, to be used for reference only.



## Nut



PART NUMBER	INTERCHANGES WITH	T TUBE O.D.	A	NH NUT HEX
DN-1	102-1	1/16	.312	5/16
DN-2	202-1	1/8	.469	7/16
DN-3	302-1	3/16	.469	1/2
DN-4	402-1	1/4	.500	9/16
DN-5	502-1	5/16	.531	5/8
DN-6	602-1	3/8	.562	11/16
DN-8	812-1	1/2	.687	7/8
DN-10	1012-1	5/8	.687	1
DN-12	1212-1	3/4	.687	1-1/8
DN-14	1412-1	7/8	.687	1-1/4
DN-16	1612-1	1	.812	1-1/2

\*NOTE: All dimensions subject to change, to be used for reference only.

## Knurled Nut



The knurled nut is used with fittings where applications of a finger tight assembly is acceptable. Common applications include, but are not limited to, low pressure laboratory use on plastic tubing.

Knurled nuts are available in the same sizes as shown for CBC-Lok® nuts (DN). The knurled nut part descriptor is DKN. For example, the part number for a 1/2" knurled nut is SS-DKN-8.




# DFC/DRC/DCSET/DNCSET

PART NUMBER	INTERCHANGES WITH	T	TUBE O.D.
DFC-1	103-1	1FF1	1/16
DFC-2	203-1	2FF2	1/8
DFC-3	303-1	3FF3	3/16
DFC-4	403-1	4FF4	1/4
DFC-5	503-1	5FF5	5/16
DFC-6	603-1	6FF6	3/8
DFC-8	813-1	8FF8	1/2
DFC-10	1013-1	10FF10	5/8
DFC-12	1213-1	12FF12	3/4
DFC-14	1413-1	14FF14	7/8
DFC-16	1613-1	16FF16	1

\*NOTE: All dimensions subject to change, to be used for reference only.

PART NUMBER	INTERCHANGES WITH	T	TUBE O.D.
DRC-1	104-1	1BF1	1/16
DRC-2	204-1	2BF2	1/8
DRC-3	304-1	3BF3	3/16
DRC-4	404-1	4BF4	1/4
DRC-5	504-1	5BF5	5/16
DRC-6	604-1	6BF6	3/8
DRC-8	814-1	8BF8	1/2
DRC-10	1014-1	10BF10	5/8
DRC-12	1214-1	12BF12	3/4
DRC-14	1414-1	14BF14	7/8
DRC-16	1614-1	16BF16	1

\*NOTE: All dimensions subject to change, to be used for reference only.



## Component Replacement Parts

Collet sets and Nut/Collet sets make for easy storage and handling of nuts and collets. CBC-Lok® component parts are precision made and should be handled with care. The components can be ordered on an arbor, which aids in careful handling and prevents them from coming off. Pinch the end of the arbor to release the components.

PART NUMBER	INTERCHANGES WITH	TUBE O.D.	QUANTITY (per arbor)
DCSET-4-10	400 Sets-10	4-ALOK-SS-SET	1/4
DCSET-6-10	600 Sets-10	6-ALOK-SS-SET	3/8
DCSET-8-10	800 Sets-10	8-ALOK-SS-SET	1/2
DCSET-12-10	1210 Sets-10	12-ALOK-SS-SET	3/4
DCSET-16-10	1610 Sets-10	16-ALOK-SS-SET	1



Nut/Collet Sets contain 5 nuts & 5 collets on an arbor.  
1/2" Nut/Collet Set part number: SS-DNCSET-8-5

PART NUMBER	TUBE O.D.	QUANTITY (per arbor)
DNCSET-4-5	1/4	5
DNCSET-6-5	3/8	
DNCSET-8-5	1/2	
DNCSET-12-5	3/4	
DNCSET-16-5	1	




## Instrument Tee

The Instrument Tee may be ordered with any standard tube or pipe size. When ordering, specify sizes in the following order:

1. Tube Size O.D
2. Female Pipe Size
3. Male Pipe Size

Example: 1/2" tube, 3/8" female pipe, 1/4" male pipe.  
SS-8-DTFM-6-4



## Heat Exchanger Tee

The Heat Exchanger Tee may be ordered in any standard tube size. The process tube is bored through. When ordering, specify sizes in the following order:

1. Jacket Tube O.D
2. Process Tube O.D. followed by "BT" for bore through designation
3. Branch Tube O.D.

Example: 1/2" tube, 1/4" tube bored through, 1/2" tube. SS-8-DTTT-4BT-8



## Thermocouple Bore Through

A Thermocouple Connector can be furnished already bored through for an additional charge. When ordering:

1. Select required size male connector. See pages 14 and 15 for a listing of available Male Connectors.
2. Add the letters "BT" to designate bore through. Example: 4-DMC-2-BT



## Tylube™ Thread Lubricant

Tylube™ is an anti-gall compound to be used on stainless steel, steel and nickel based alloys. Temperature range to 500°F. Not recommended for plastic and aluminum products. Tylube™ is made from distilled water with inert ingredients and contains no silicones, heavy metals, chlorine or sulfur. For a complete list of ingredients request an MSDS to be sure of its compatibility with your installation. Available in 8 oz. plastic bottles.




## CBC-Lok® Installation Instructions

CBC-Lok® Tube Fittings come completely assembled and ready for use, no disassembly required. Although there are some general guide lines to follow no special preparation of the tubing is necessary, reference page 44. In overhead applications Tylok recommends using a Pre-Set Tool, see page 47.


Size		Tighten # Turn(s)
1	1/16"	3/4
2	1/8"	
3	3/16"	
4	1/4"	1-1/4
5	5/16"	
6	3/8"	
8	1/2"	
10	5/8"	
12	3/4"	
14	7/8"	
16	1"	

Size #1 Thru #3  
(1/16" - 3/16")




Finger Tight Plus  
3/4 Turn

Size #4 Thru #16  
(1/4" - 1")



Finger Tight Plus  
1-1/4 Turns




Simply insert the tubing into the assembly making sure the tubing seats firmly against the shoulder of the body and the nut is finger tight.




Tighten nut with wrench an additional number of turns indicated above, while holding the fitting body with a second wrench.

## To Remove Tube and Re-Connect Tube Fitting

Mark the location of the nut with reference to the body before disassembly. For reassembly, re-insert the tubing into the body until it is seated. With proper size wrench, retighten nut to original location by realigning previous marks. A noticeable amount of torque will develop when the nut is turned to original position. Next, rotate the nut slightly past original position to fully re-set the seal.



Mark the location of the nut with reference to the body.



Back off the nut until it is clear of the body and remove the tubing from the fitting.

## CBC-Lok® Tubing Selection & Preparation

Proper selection of tubing is key to the performance of the fitting. When selecting the proper wall thickness and material, all tubing should be compatible with the process fluid, temperature, application, flow and system pressure.

For proper sealing it is recommended that the tubing and fitting be of like material to allow for positive sealing (i.e., stainless on stainless, brass on copper, steel on steel). Galvanic corrosion could occur if the tubing and fitting are not of like material, with the exception of a brass fitting on copper tubing.

When using stainless steel tubing, Tylok recommends using Type 304 or 316 fully annealed, seamless or welded redrawn meeting ASTM-A-213, ASTM-A-269 or equivalent, with a suggested maximum hardness of 80 Rb.

For copper tubing, Tylok suggests using soft annealed, seamless tubing per ASTM-B75 or equivalent. Copper water tube type K or L, soft annealed (Temper O) per ASTM-B88 can also be used.

When using carbon steel, all tubing should be fully annealed and conform to ASTM-A-179, or equivalent, with a maximum hardness of 72 Rb.

In general, all tubing should be free of nicks, scratches, imperfections of any kind and be suitable for bending. Out of round tubing that does not easily go through fitting components should not be used. It is recommended that the charts be used for tube selection. Ideally, the tube end should be cut square so that when it bottoms out inside the fitting an extra seal is provided. Avoid installing contaminated tubing into your system. For elevated temperatures see page 46.

CBC-Lok® Tube Fittings swage the tubing to achieve its seals. Thin wall tubing (wall thicknesses with working pressures highlighted in reverse text, in the charts) is not recommended for Gas Service. For Gas Service see page 45.

When using tubing of a thinner or thicker wall than shown, it is always recommended that you consult with your local Distributor or contact Tylok International directly if there is any doubt selecting tubing.

Values in reverse text are not recommended for Gas Service.

*Note: Tables, calculated to the right, are suggested maximum working pressure ratings, in accordance with ASME B31.3, but should be used for reference only. Tylok International, Inc., is not responsible for its accuracy nor designs using these figures. All compatible Tylok fittings will withstand pressures above those listed for maximum tubing working pressures.*

It is the responsibility of the Engineer to refer to the technical pages in this catalog to ensure selection of the proper tubing material, tubing compatibility with the fitting, media and tubing wall thickness. Following the stated recommendations will ensure a safe application, free of leaks. The entire system must be considered when selecting the tube.

### SUGGESTED ALLOWABLE WORKING PRESSURE TABLES (psig)

Stainless Steel								
Tube Size O.D.	Tube Wall Thickness (inches)							
	.028	.035	.049	.065	.083	.095	.109	.120
1/8"	8400	10600						
3/16"	5500	7000	10100					
1/4"	4000	5100	7500	10100				
5/16"		4100	5900	8000				
3/8"		3300	4800	6600				
1/2"		2600	3800	5100	6700			
5/8"			3000	4000	5200	6100		
3/4"			2500	3300	4300	5000	5800	
7/8"			2100	2800	3600	4200	4900	
1"				2400	3200	3700	4200	4700

75,000 PSI Tensile

*Note: For welded and drawn tubing, a derating factor must be utilized. For double welded tube, multiply the above pressure rating by .85; and for single welded tube by .80 (ANSI B 31, Table A-1B).*

Carbon Steel								
Tube Size O.D.	Tube Wall Thickness (inches)							
	.028	.035	.049	.065	.083	.095	.109	.120
1/8"	8100	10200						
3/16"	5200	6700	9600					
1/4"	3800	4900	7100	9600				
5/16"		3800	5500	7600				
3/8"		3100	4500	6200				
1/2"		2300	3300	4500	6000			
5/8"			2600	3500	4600	5350		
3/4"			2200	2900	3800	4400	5100	
7/8"			1800	2500	3200	3700	4300	
1"				2100	2800	3200	3700	4200

47,000 PSI Tensile

Copper								
Tube Size O.D.	Tube Wall Thickness (inches)							
	.028	.035	.049	.065	.083	.095	.109	.120
1/8"	2700	3600						
3/16"	1800	2300	3500					
1/4"	1300	1700	2500	3600				
5/16"		1300	2000	2800				
3/8"		1100	1600	2300				
1/2"		800	1200	1700	2200			
5/8"			900	1300	1700	1900		
3/4"			800	1000	1400	1600	1900	
7/8"			600	900	1100	1300	1600	
1"			600	800	1000	1200	1400	1500

30,000 PSI Tensile

## Gas Service

Extra care must be taken when tubing is used in gas service applications. Small gas molecules easily escape through minute leak paths, therefore, the tubing must be free of nicks, scratches and imperfections of any kind. In particular, when using large diameter tubing the possibility of surface defects is increased due to greater surface area. It is strongly recommended that the heavier wall thicknesses be selected. Penetration of the ferrules on thin wall tubing or soft material may not offer enough radial resistance for sealing. In such cases, Tylok recommends using a Plane Insert (Part descriptor DPI, page 39). In the tables on page 44 note the suggested allowable working pressure for gas service.

Values in reverse text are not recommended for Gas Service.

## Precautions for Weld Ends

CBC-Lok® Tube Fittings with weld ends offer the same positive sealing as all other Tylok fittings. Welding could deform the assembly, making pull ups or disassembly difficult. Some precautions should be taken...

- Remove the nut and ferrules from the fitting
- It is important that the fitting threads and sealing surfaces be protected from weld splatter
- A heat sink should be used to dissipate heat
- Ensure alignment by tack welding symmetrically
- Once welded, remove the weld splatter protection and reassemble nut and ferrules on fitting

## Tyspy Leak Detector

Tylok offers a leak detector, Tyspy, for use in all sealing applications. Tyspy meets standard MIL-L-25567D, Sect. 4.4.9 for use on oxygen systems. Available in 1 pt. spray bottles. Specify number of bottles needed when ordering. Part Number: TYSPY

- All temperature formula: -55°F to 200°F
- Ultra-sensitive
- Long-lasting bubbles
- Available in spray bottle
- Fluorescent for improved visibility
- Safe for oxygen systems
- Non-corrosive, non-toxic

## Gap Gages

Gap Gages can be purchased to ensure the Installer and Inspector that the nut has been properly tightened. Available upon request.

Part Number	Tube Size	Part Number	Tube Size
#1-DGG	1/16"	#8-DGG	1/2"
#2-DGG	1/8"	#10-DGG	5/8"
#3-DGG	3/16"	#12-DGG	3/4"
#4-DGG	1/4"	#14-DGG	7/8"
#5-DGG	5/16"	#16-DGG	1"
#6-DGG	3/8"		



When fitting is properly tightened, gap gage should not fit between nut and shoulder of body.

## Safety Guidelines

- Never connect, disconnect or remake a fitting with pressure in the system
- Make sure all fittings are properly installed, reference Installation Instructions - page 43, before pressurizing the system
- Tubing material should be softer than fitting material
- Tylok recommends using Tylok replacement parts
- Although the fittings will hold to the pressure rating of the tubing, it is not recommended to go beyond this rating. Elongation could occur in the tubing, shrinking the wall thickness and causing potential harm to anyone in the area
- Always use proper thread lubricants and sealants on tapered pipe threads
- If process fluids are toxic and/or hazardous, exercise extra caution
- Never bleed a system by loosening a fitting
- For proper sealing it is recommended that the tubing and fitting be of like material

## Quality Control

All components are manufactured and inspected to meet strict quality control standards in each phase of production. All employees are thoroughly trained to follow rigid procedures, in accordance with the ISO 9001:2000 Quality Standard, to ensure a quality product from the start of each job through completion. At Tylok our primary concern is quality, reliability and service to our customers.



## Heat Traceability

CBC-Lok® Tube Fittings are completely heat code traceable back to the original mill heat from which it was made. Starting with the original billet, the mill creates a certificate which completely describes the chemical and physical makeup. For any one of the four components (body, front ferrule, rear ferrule, nut) the material certifications can be provided when calling Tylok and giving the heat code stamp marked on the part itself, along with the part number.

## Raw Material Specifications


Fitting Material	Bar Stock	Forging	*Tubing Specification	Maximum Specification Hardness (Tubing)
Brass	ASTM-B16 Alloy 360 ASTM-B453 Alloy 345	ASTM-B124 Alloy 377	ASTM-B75 Copper (Temper O)	60 Max. Rockwell 15T
Stainless Steel	ASTM-A276 ASME-SA-479 Type 316-SS	ASME-SA-182 Type 316-SS	ASTM-A213 ASTM-A269	90 Rb
Steel	ASTM-A108		ASTM-A179	72 Rb

\*Reference Tubing Selection & Preparation, page 44.

## Tylok Pre-Setting Tool

The CBC-Lok® product line offers a Pre-Setting Tool when fittings need to be installed in hard to reach places. The Pre-Setting Tool is designed to be used in any tabletop vice. After tightening the nut the specified number of turns, as stated in the included installation instructions, loosen the nut from the Pre-Setting Tool. Once the ferrules have swaged into the tubing surface, the assembly is ready for installation.

When ordering the CBC-Lok® Pre-Set Tool, reference the part number in the chart. The Pre-Set Tool is hardened for maximum durability. The Pre-Set Tool can be used repeatedly to set the ferrules onto the tubing for easy installation.



Part Number	Tube Size
#1-DPST	1/16"
#2-DPST	1/8"
#3-DPST	3/16"
#4-DPST	1/4"
#5-DPST	5/16"
#6-DPST	3/8"
#8-DPST	1/2"
#10-DPST	5/8"
#12-DPST	3/4"
#14-DPST	7/8"
#16-DPST	1"




Place Pre-Setting Tool in a vice and tighten nut specified number of turns.



Back nut off of Pre-Setting Tool. Notice the ferrules have swaged into the tubing. Now take tubing to installation area.

## Tube Insertion Chart

For pre-cutting tubing to length, the following chart shows the additional length inside the fitting assembly.



Tube Size	T Tube O.D.	B Dimension
#1	1/16	.34
#2	1/8	.51
#3	3/16	.54
#4	1/4	.60
#5	5/16	.64
#6	3/8	.67
#8	1/2	.90
#10	5/8	.96
#12	3/4	.96
#14	7/8	1.03
#16	1.0	1.24

\*NOTE: All Dimensions Subject to Change.

## Tubing-General Applications

CBC-Lok® Tube Fittings are designed to perform in a variety of applications that demand high performance. The CBC-Lok® product line has been engineered to provide optimal performance, however tubing should always be considered as an important factor in the design stages of any system. Below is a table that describes some general uses for different types of materials. The table is provided as a reference to the Engineer in the design process.

Tylok suggests the use of seamless, fully annealed tubing. Welded tubing may be used with Tylok fittings. However, due to the manufacturing of welded tubing, variables may be encountered. The media flowing through the tubing must be compatible with the tubing itself. It is always a good rule to use like tubing material on like fitting material. If this format is not followed, the ferrules may have difficulty penetrating the tubing causing an adverse affect on the sealing ability. In addition, dissimilar materials in contact may be sensitive to galvanic corrosion. Tylok recommends ordering tubing material to meet ASTM specifications to ensure that it will be dimensionally, physically and chemically within precise limits (see Raw Material Specifications chart - page 47).

Tubing Material	General Applications	Recommended Temperature Range
Carbon Steel	Air Lines, High Pressure, High Temperature, Oil, Air, Specialty Chemicals, Hydraulic Gases	-20°F to 400°F*
Copper	Low Temperature, Low Pressure Water, Oil, Air, Pneumatic Controls, Lube Lines	-40°F to 400°F
Stainless Steel	High Pressure, High Temperature, Nitrogen, Helium, Flammable Gases, Hydraulic, Gases, generally corrosive media	-20°F to 1000°F

\*Based on 400°F maximum.

## Notice

In designing a system incorporating tube fittings and valves, it is the designer's or user's obligation and responsibility to determine the appropriate fittings and valves to be used for each application, and to insure proper installation and maintenance.

## Limited Warranty

Tylok fittings and valves are warranted solely against defects in material and workmanship in the performance of the specific functions for which they are designed, as set forth in the published specifications for a period of 12 months. Should any fitting and valve or its component fail due to a defect in material or workmanship, Tylok will replace said fitting and valve without charge upon return of the failed part and evidence of its failure being due to materials or workmanship.

The Warranty above set forth is the only warranty applicable to Tylok products, and is in lieu of any and all other warranties either express or implied, including any warranty of merchantability or fitness. Tylok's sole responsibility or liability as a result of any loss or damage due to failure shall be to replace the failed part or fitting and valve, and it shall bear no liability for any incidental or consequential damages to person or property.



## Our History

In the mid 1940s, Cullen Crawford founded the Crawford Fitting Company. Mr. Crawford developed and patented the original flareless fitting (nut and two ferrule system), for the Crawford Fitting Company. Thus, a new and innovative industry was born making it far easier to make tubing connections. This reduces installation time and errors. Since his invention, End Users from all four corners of the globe have made billions of connections. This system provides leak proof seals and thus Mr. Crawford has been named "The founder of the flareless fitting."

## Our Mission

It is our mission, at Tylok International, Inc., to continuously strive for and achieve total customer satisfaction with both our products and services.

## Our Goal

Tylok's aggressive goal is to establish ourselves as an industry leader and expand our market share. This is maintained in every department within the organization. Our "total effort" will guard against losing the personal touch that makes our business enjoyable and prosperous for all involved.

## INSTRUMENTATION TUBE FITTINGS

### Tylok Standard

CBC-Lok®

CS-Lok®

### PIPE FITTINGS

### WELD FITTINGS

### BALL VALVES

- Ty-Flo® HP Series
- Ty-Flo® 3 Piece

### NEEDLE VALVES

### MANIFOLDS

### FLEXIBLE METAL HOSE



1061 East 260th Street • Euclid, Ohio 44132  
Tel: (216) 261-7310 • 1-800-321-0466 • Fax: (216) 261-7317  
info@tylok.com  
www.tylok.com